



Features:

- Available with LED or MR16 halogen lamps.¹
- Precision machined from aluminum or brass with stainless steel hardware.
- Removable cap available in three cutoff styles.
- Each cap holds up to three lens accessories.
- Thick walled cap and optimized high temperature silicone O-ring placement prevents leaking.
- Large cap set screw prevents stripping.
- Various mounting canopy options allow for surface mounting or mounting on industry standard round and rectangular junction boxes.
- CSA tested & certified to US & Canadian safety standards for use in wet locations.

1. Available lamp wattage varies by material and mounting method.




Photo: DL1A with BL finish and C2 cap, mounted on an MO3 canopy with 3" stem.

Model **DL1**

Low Voltage
MR16 Halogen (50W)
LED (2W)



- Ø2 3/8" body, 3 7/8" maximum body length.
- Aluminum and brass.
- Remote transformer required.

Accessories:



Lenses & Baffles
(Model AC3)



Adjustable Cutoff Shrouds
(Models AC4 & AC5)



Machined Stems
(Model AC1)



Electronic Transformer
(Model XM3)



Magnetic Transformer
(Model XM2)

Mounts:



Wall Canopies
(Models MO3, MO4, & MO15)



Cast Box & Covers
(Models MO5 & MO6)



Powered Canopy
(Model MO12)