

Specifications:

Housing: Stake and Junction housings made from corrosion resistant, thermoplastic PVC. Junction housing is supplied with two integral 1/2" slip fittings allowing for conduit connection, leak proof cable entry, and feed through wiring. (Conduit and cable not included).

Cap: Cap machined from 6061-T6 aluminum, C36000 brass, or 304 stainless steel. Cap contains a 1/2" NPS threaded mounting hole, and is locked to housing with three 18-8 stainless steel set screws.

Stem: Stems are machined from 6061-T6 aluminum, C36000 brass, or 304 stainless steel; and are threaded 1/2" NPS on both ends. Stem option available in lengths of 3", 6", 12", 18", 24", 30", 36", 42", and 48".


Seals: O-ring groove on cap allows for use of an O-ring to prevent leaking between cap and fixture knuckle. (Note: All Vision3 fixtures come with a high temperature, black Viton O-ring on the knuckle for this purpose). On styles S3 and S4, a silicone O-ring between the cap and housing ensures a watertight

junction housing.

Finish: TGIC thermo set polyester powder coat paint available in 14 standard colors. On aluminum model, finish is applied over a corrosion resistant chromate conversion coating. Aluminum model available in one additional metal finish: Clear Anodized. Brass model available in three additional metal finishes: Natural, Polished, and Aged. Stainless steel model available in three additional metal finishes: Natural, Polished, and Brushed.

Electrical: Style S3 transformer option includes a 75VA, 11.6V output, electronic transformer in 120V, 230V, or 277V input. Transformer mounted to cap with a 304 stainless steel bracket and 18-8 stainless steel hardware.

Certification: CSA tested & certified to US and Canadian safety standards for wet location landscape use per UL 1838 (all except 230V model).



Ordering Information:

Model	Finish	Style	Transformer Input Voltage	Stem
MO1A - Aluminum	BL - Black	S0 - No Mount (Cap Only)	0 - No Transformer (Styles S1, S2, and S4 only)	0 - No Stem
MO1B - Brass	BLT - Textured Black	SM - Surface Mount	120 - 120 Volt Input (Style S3 only)	3 - 3" Stem
MO1S - Stainless	BN - Bronze		230 - 277 Volt Input (Style S3 only)	6 - 6" Stem
	BNT - Textured Bronze	S1-12 - 12" Stake (Available with up to 36" stem only)	277 - 277 Volt Input (Style S3 only)	12 - 12" Stem
	BAT - Textured Bark	S1-18 - 18" Stake (Available with up to 36" stem only)		18 - 18" Stem
	WI - White			24 - 24" Stem
	GRT - Textured Green	S2-12 - 12" Adjustable Stake (Available with 12" stem only)		30 - 30" Stem
	SI - Silver	S2-18 - 18" Adjustable Stake (Available with 18" stem only)		36 - 36" Stem
	GY - Grey	S2-24 - 24" Adjustable Stake (Available with 24" to 48" stem)		42 - 42" Stem
	BE - Beige	S3-12 - 12" Junction with Transformer (Available with up to 36" stem only)		48 - 48" Stem
	GNT - Textured Granite	S3-18 - 18" Junction with Transformer (Available with up to 36" stem only)		
	SAT - Textured Sand			
	PAT - Textured Patina	S4-12 - 12" Junction (Available with up to 36" stem only)		
	EAT - Textured Earth	S4-18 - 18" Junction (Available with up to 36" stem only)		
	CLA - Clear Anodized (MO1A only)			
	NAT - Natural (MO1B & MO1S only)			
	POL - Polished (MO1B & MO1S only)			
	AGE - Aged (MO1B only)			
	BRU - Brushed (MO1S only)			

Notes:

- Specifications, certifications, and ordering information are subject to change. Please check website for latest specification sheets.

Example: **MO1S - POL - S1-18 - 0 - 6**