



**Features:**

- Available with LED, halogen (MR16, PAR16, PAR20), metal halide (PAR20), and compact fluorescent (PAR20) lamps.<sup>1</sup>
- Precision machined from aluminum or brass with all stainless steel hardware.
- Stem is permanently attached to a thick walled canopy to prevent 'sagging'.
- 'Rotate & Lock' double taper knuckle features a full 360° of lockable rotational aiming.<sup>2</sup>
- Removable cap available in four cutoff styles.<sup>1</sup>
- Each cap holds up to three accessories.
- Various mounting canopy options allow for surface mounting or mounting on industry standard round and rectangular junction boxes.
- CSA tested & certified to US & Canadian safety standards for use in wet locations.

1. Available lamp & cap style varies by model.  
 2. Knuckle is protected under U.S. Patent #6,966,679.



Photo: SL1A with BL finish and C1 cap, mounted on an MO3 canopy with an 18" stem.

Model **SL1**  
Low Voltage  
**MR16 Halogen (50W)**  
**LED (2W)**

Model **SL4**  
Line Voltage  
**MR16 Halogen (75W)**  
**LED (2W)**

Model **SL2**  
Line Voltage  
**PAR16 Halogen (75W)**  
**PAR20 Halogen (50W)**  
**Fluorescent (9W)**  
**LED (2½W)**

Model **SL3**  
Low Voltage  
**MR16 Halogen (75W)**  
**LED (2W)**

Model **SL5**  
Metal Halide  
**PAR20 (39W)**



- Ø2 3/8" head.
- Remote transformer required.



- Ø3 1/8" head.
- Integral magnetic transformer.



- Ø3 1/8" head.
- Remote transformer required with Model SL3.
- Ballast required with Model SL5.

**Accessories:**



Lenses & Baffles  
(Model AC3)



Adjustable Cutoff Shrouds  
(Models AC4 & AC5)



Machined Stems  
(Model AC1)



Electronic Transformer  
(Model XM3)



Magnetic Transformer  
(Model XM2)

**Mounts:**



Wall Canopies  
(Models MO3, MO4, & MO15)



Cast Box & Covers  
(Models MO5 & MO6)



Powered Canopy  
(Models MO12 & MO13)

**Ballasts:**



In-grade Remote Ballast  
(Model BM3)



Wall Mount Ballast Canopy  
(Model BM6)



Wall Mount Remote Ballast  
(Model BM4)