

Model WM1 Low Voltage MR16 Halogen (50W) LED (2W)



C1 Cap

Model WM4

Line Voltage

LED (2W)

MR16 Halogen (75W)

- Ø2 3/8" body, 4 15/16" maximum overall length.
- Aluminum, brass, and stainless steel.
- Remote transformer required.
- · ADA compliant.

- Ø3 1/8" body, 8 3/4" maximum overall length.
- Aluminum and brass.

C2 Cap

- Integral magnetic transformer.
- ADA compliant.

Model WM13

Line Voltage PAR30 Halogen (75W) PAR38 Halogen (120W) Fluorescent (23W)

Model WM14

Metal Halide PAR30 (70W) PAR38 (150W)



Model WM2

Line Voltage PAR16 Halogen (75W) PAR20 Halogen (50W) Fluorescent (9W) **LED** (21/2W)

Model WM3

Low Voltage MR16 Halogen (75W) **LED** (2W)

Model WM5

Metal Halide PAR20 (39W)



- Ø6 1/2" body, 9 7/8" overall length.
- Aluminum only.
- Ballast required with Model WM14.

- Ø3 1/8" body, 7 3/4" maximum overall length.
- Aluminum and brass.

C2 Cap

- Remote transformer required with Model WM3.
- Ballast required with Model WM5.
- ADA compliant.

Accessories:



Lenses & Baffles (Model AC3)



Adjustable Cutoff Shrouds (Models AC4 & AC5)



Electronic Transformer (Model XM3)



(Model XM2)







Cast Box & Covers (Models MO3, MO4, & MO15) (Models MO5 & MO6)

Powered Canopy (Models MO12 & MO13)

Ballasts:





Wall Mount Remote Ballast



©2006 Vision3 Lighting®