

Model AC1 - Machined Stems

(see Model AC1 spec sheet)



Features:

- Precision machined from aluminum, brass, or stainless steel.
- Industry standard 1/2" NPSM mount threads on each end.
- Available in standard lengths of 3", 6", 12", 18", 24", 30", 36", 42", and 48" (other lengths available upon request).
- Available with a 304 stainless steel nipple for use with other mount options.

Model AC2 - Machined Lock Nut

(see Model AC2 spec sheet)



Features:

- Precision machined from aluminum, brass, or stainless steel.
- Threads on to any Ø1" fixture knuckle, with 1/2" NPSM threads, for mounting to a wall canopy.
- Allows for rotational aiming and locking of a fixture from outside the mounting canopy.

Model AC3 - Lens Accessories

(see Model AC3 spec sheet)



Features:

- Tempered glass color filters, lenses, or louver options to accomplish the desired lighting effect with your Vision3 Lighting luminaire.
- Stainless steel accessory clip available to secure your lens accessories in place.
- Lens accessories may be specified within the catalog logic for most fixtures, or ordered separately.
- Custom color and dichroic filters are available upon request.

Model AC4 - FL1 Adjustable Cutoff Shield

(see Model AC4 spec sheet)



Features:

- Precision machined from aluminum, brass, or stainless steel.
- Allows for adjustable light cutoff on Vision3 Lighting MR16 fixtures with an outer diameter of Ø2 3/8", such as FL1, FL11, SL1, SL6, WM1, WM6, DL3, etc.
- Weep hole and flow thru design minimizes water and debris collection in the cap.
- Ø2 3/4" cap X 4 1/8" long (C4 style) or 2 1/4" long (C2 style).

Model AC5 - FL2 Adjustable Cutoff Shield

(see Model AC5 spec sheet)



Features:

- Precision machined from aluminum, brass, or stainless steel.
- Allows for adjustable light cutoff on Vision3 Lighting MR11 fixtures with an outer diameter of Ø1 3/4", such as FL2, DL2, etc.
- Weep hole and flow thru design minimizes water and debris collection in the cap.
- Ø2" cap X 3 1/2" long (C4 style) or 2" long (C2 style).

Model XM2 - Multi-Tap Magnetic Transformer

300W, 600W, 1000W, and 1200W.

(see Model XM2 spec sheet)



Features:

- 120V input magnetic transformer is available in 300W, 600W, 1000W, or 1200W with 11V, 12V, 13V, 14V, and 15V outputs.
- Terminal strip allows quick and easy wiring.
- Rain tight stainless steel NEMA 3R type enclosure with lockable hinged door and knockouts for conduit connection.
- Stainless steel hardware and mounting brackets.
- Photocell and timer options can be field installed.
- U.L. listed Landscape Lighting Transformer.

Model XM3 - Electronic Transformers

120V & 277V, 75W & 150W.

(see Model XM3 spec sheet)



Features:

- 120VAC and 277VAC input electronic transformers available in 75W and 150W with 11.6VAC output.
- Electronic circuitry encapsulated in a flame retardant plastic casing to withstand harsh and damp conditions.
- Dimmable (120VAC models only)
- U.L. & CSA certified.