

# METALWORKS™ – Standard

Tegular

smooth texture



METALWORKS Unperforated

METALWORKS Tegular Microperforated with SUPRAFINE™ 9/16" Exposed Tee grid.

## Color Selection

Due to printing limitations, shade may vary from actual product.



White (WH)



Silver Grey (SG)



Gun Metal Grey (MY)

## Detail



METALWORKS Tegular Microperforated



METALWORKS Tegular Extra Microperforated



METALWORKS Tegular Faceted Applications

For more information about faceted applications with square tegular panels in 15/16" grid, refer to CS-3701 and installation instructions on our web site at [armstrong.com/metalworks](http://armstrong.com/metalworks), search keyword (example: faceted).

For tegular panels, a Faceted Hold-down Clip must be used, which will limit accessibility. If accessibility is required in a faceted application, use Vector panels.



# METALWORKS™ – Standard

Tegular

smooth texture

Recycled Content: 25%

## Key Selection Attributes

- 100% upward access
- Ideal for renovation using standard 15/16" or 9/16" Exposed Tee grid systems
- Durable
  - Scrubbable
  - Soil-resistant
  - Washable
- Cutouts for recessed lights and sprinklers available

## Typical Applications





















- Lobbies and corridors
- Retail
- Hospitality
- Office and healthcare
- High access areas

## Colors

White (WH)  
Silver Grey (SG)  
Gun Metal Grey (MY)

## Visual Selection

## Performance Selection

Grid Face	Edge Profile	Item * Number	Dimensions		Acoustics		Factory Mutual Certified Flame Spread/ Smoke Developed	Light Reflect	Durable		
					NRC	CAC					
METALWORKS Flush Tegular											
15/16"	Flush Tegular	9442U6A1_♦♦	2 x 2' unperforated		0.10	36	25-50	0.77	Scrub	Soil	Wash
		9444U6A2_♦♦	2 x 2' microperforated with plain border and acoustical fleece		0.65 0.90**	38*	25-50	0.61	Scrub	Soil	Wash
METALWORKS 5/16" Square Tegular											
15/16"	Square Tegular	9683U6A1_	2 x 2' unperforated		0.10	36	25-50	0.77	Scrub	Soil	Wash
		9685U6A2_	2 x 2' microperforated with plain border and acoustical fleece		0.65 0.90**	38*	25-50	0.61	Scrub	Soil	Wash
		4704U6A2_♦♦	2 x 2' extra microperforated with acoustical fleece		0.65 0.90**	40*	25-50	0.77	Scrub	Soil	Wash
9/16"	Square Tegular	9320U6A1_	2 x 2' unperforated		0.10	36	25-50	0.77	Scrub	Soil	Wash
		9324U6A2_	2 x 2' microperforated with plain border and acoustical fleece		0.65 0.90**	38*	25-50	0.61	Scrub	Soil	Wash
		2184U6A2_	2 x 2' extra microperforated with acoustical fleece		0.65 0.90**	40*	25-50	0.77	Scrub	Soil	Wash
METALWORKS 5/8" Square Tegular											
15/16"	Square Tegular	9680U6A1_♦♦	2 x 2' unperforated		0.10	36	25-50	0.77	Scrub	Soil	Wash
		9682U6A2_♦♦	2 x 2' microperforated with plain border and acoustical fleece		0.65 0.90**	38*	25-50	0.61	Scrub	Soil	Wash
9/16"	Square Tegular	4700U6A1_♦♦	2 x 2' unperforated		0.10	36	25-50	0.77	Scrub	Soil	Wash
		4702U6A2_♦♦	2 x 2' microperforated with plain border and acoustical fleece		0.65 0.90**	38*	25-50	0.61	Scrub	Soil	Wash

\* With optional field-cut #747 mineral fiber backing

\*\* NRC 0.90 with optional fiberglass infill (#8200100)

♦ When specifying or ordering, include the appropriate color suffix (WH, SG or MY) with the item number. Light reflectance is for white only.

♦♦ "S" Service item with 1,000 SF minimum order quantity and extended lead time.

## Physical Data

### Material

Electrogalvanized Steel – thickness .021"

### Surface Finish

Factory-applied powder-coated finish (post-coated)

### Fire Certification

Factory Mutual Approvals  
Specification Tested per ASTM E 84 and CAN/ULC S102

### ASTM E 1264 Classification

Fire Class – Class A  
9683U6A1\_\_, 9320U6A1\_\_,  
9680U6A1\_\_, 4700U6A1\_\_,  
9442U6A1\_\_ - Type XX  
(unperforated steel panels) Pattern G  
9685U6A2\_\_, 9324U6A2\_\_,  
9682U6A2\_\_, 4702U6A2\_\_,  
9444U6A2\_\_, 4704U6A2\_\_,  
2184U6A2\_\_ - Type XX  
(microperforated steel panels) Pattern C

### Backloading Recommendation

Contact TechLine for specific information

### Weight; Square Feet/Cartron

See product details at [armstrong.com/ceilings](http://armstrong.com/ceilings)

### Warranty

1-year limited warranty. See warranty details at [armstrong.com/ceilings](http://armstrong.com/ceilings)

### Recommended Suspension System

Items	Suspension System
9442U6A1WH, 9444U6A2WH	15/16" PRELUDE® XL
9680U6A1WH, 9682U6A2WH, 9683U6A1WH, 9685U6A2WH, 4704U6A2WH	15/16" PRELUDE XL
4700U6A1WH, 4702U6A2WH	9/16" SUPRAFINE™
2184U6A2WH, 9320U6A1WH 9324U6A2WH	9/16" SUPRAFINE 9/16" SILHOUETTE® 9/16" INTERLUDE® XL 9/16" SONATA™ 9/16" TRIMLOK®

TechLine™ / 1 877 ARMSTRONG  
1 877 276 7876

[armstrong.com/ceilings](http://armstrong.com/ceilings) (search: metalworks)

CS-3269-207

© AWI Licensing Company, 2007 • Printed in the United States of America • 10% post consumer waste. Printed with vegetable inks.  Recyclable.