


Submitted Model No.:______Specific Features:_____

5 3/16" (132 mm) 360° Swing Spout 7 3/8" (187 mm) 4 3/16" (105 mm) 1/2"-14 NPSM 1 15/16" (49 mm) 3/8" (35 mm) Max. Deck Thickness 4" Centers (102 mm) 2 7/16" (60 mm) 6 3/16" (156 mm) 1 5/8" (42 mm) to 2 3/8" (61 mm) 2 1/8" (54 mm) Dia. 3 3/8" (86 mm) 匣 1 3/8" (35 mm) Dia. 4 5/8" (118 mm) 1 1/4" (32 mm) Dia.

Available LHP
Handle Options
▲Designate proper
finish suffix



Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselectonline.com for finish options and product availability.

ODELTA

LAVATORY FAUCETS

- Orleans[™] Bath Series
- Two Handle Deck Mount
- 3 Hole Sink Applications
- 4" Centerset

STANDARD SPECIFICATIONS:

- Solid brass fabricated body.
- 4" (102 mm) centerset.
- 5 3/16" (132 mm) long, 7 3/8" (187 mm) high spout swings 360°.
- LHP-Less Handle Program. See handle options below.
- 1/4 turn handle stops.
- Hot and cold stems are interchangeable.
- Control mechanism is the rotating cylinder type with stainless steel plate and 180° rotation, with replaceable non-metallic seats operating in stainless steel lined sockets.
- 1/2"-14 NPSM threaded male inlet shanks.
- Models have metal drain with pop-up type fitting with plated flange and stopper.

WARRANTY


- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.





COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Indicates ADA compliance to ICC/ANSI A117.1





55 E. 111th Street, Indianapolis, IN 46280 395 Matheson Blvd. E., Mississauga, ON L4Z 2H2 © 2006 Masco Corporation of Indiana