

Single Layer Thin Terrazzo Tile **WAUSAU TILE**

America's One Source™



800.388.8728 • www.wausautile.com

The ease and versatility of installation alone are enough to make our Thin Terrazzo Tile the choice of installers.



Ronald Reagan Washington National Airport
Washington, DC

Why Choose Wausau Terrazzo Tile?

1. Design Flexibility

With 79 standard colors and 4 different styles to choose from, you can turn creative ideas into colorful reality with precast terrazzo tile. Shapes, designs, logos and custom lettering are possible, and limited only by your imagination, through Wausau Tile's water jet technology.

2. Speed and Ease of Installation

Precast terrazzo, unlike poured terrazzo, installs in less time, with less mess, and can save up to 30% in overall cost.

3. Ease of Maintenance

Precast terrazzo tile is easy to maintain without the use of harsh or expensive cleaners and solvents.

4. Made in the U.S.A.

Wausau Tile, a company with over 50 years of experience, manufactures terrazzo tile in the United States.

5. Warranty

Up to a 5-year warranty is available on terrazzo tile when installed with Wausau Tile's mortar mix.

6. Customer Service

Knowledgeable and experienced sales staff, dedicated to providing exceptional customer service.

Flooring Materials Cost Comparison

Costs per Square Foot	Installed Cost	Annual Maintenance Cost	Years Average Life	Replacement Cost	Total Expenditure 40 Years	Cost per Year
Vinyl Sheet Flooring	2.72	1.39	9	3.43	73.57	1.84
Carpet	1.93	1.53	10	2.24	72.09	1.80
Vinyl Tile Flooring	1.23	1.47	15	1.60	64.27	1.61
Porcelain Tile	6.78	1.22	40	0.00	55.58	1.38
Ceramic Mosaic Tile	6.48	1.22	40	0.00	55.28	1.38
Quarry Tile	5.78	1.22	40	0.00	54.58	1.36
Terrazzo Tile	8.50	0.58	40	0.00	31.70	0.78



Affordability is a definite consideration when choosing a floor. Add the beauty of Terrazzo Tile, and you have an unbeatable combination.



Durability and ease of care, year after year, are sufficient reasons for property owners to choose Wausau Tile's Thin Terrazzo Tile.



Department of Motor Vehicles
Las Vegas, NV




In an effort to be environmentally conscious, Wausau Tile has introduced "recycled glass" terrazzo tile. In addition to the brilliant colors this process makes available, recycled glass products from Wausau Tile qualify for Green Status and LEED certification.

Belvidere Oasis, Chicago, IL

WM Micro & WA Micro Accent Style Terrazzo Tile

Standard Sizes



24" x 24"

16" x 16"

12" x 12"



WM724 - Type 1




WM720 - Type 1



WM722 - Type 2



WM725 - Type 1



WM728 - Type 1



WM729 - Type 2




WA700 - Type 2



WA705 - Type 3

WM727
Type 1




WA704
Type 2



Terrazzo tile colors shown are only a representative of the actual colors. Request samples for approved colors.

WM Micro is available in 14 standard colors. The micro style uses 3/16"-minus aggregates. The smaller-sized aggregate makes the overall color of the matrix more defined and rich. Custom colors are available. Prices quoted upon request.


WM Micro & WA Micro Accent Style Terrazzo Tile



WA706 - Type 2



WM735 - Type 1



WM734 - Type 1



WM726 - Type 1



WM731 - Type 1




WA707 - Type 3




WM730 - Type 1




WA702 - Type 3



WM733
Type 1



WM732
Type 2



WA701
Type 3

WA Micro Accent is available in 7 standard colors. A combination of 3/16"-minus marble and inorganic cement coloring is used to create some of the brightest accent colors in the cementitious terrazzo industry, giving the designer more options. Accent tile standard sizes include 3" x 12", 6" x 12", 12" x 12", 16" x 16", or 24" x 24". Custom colors available. Prices quoted upon request.

WT Traditional Style Terrazzo Tile

WT777

Type 1

WT779

Type 1

WT765

Type 1

WT781

Type 1

WT778


Type 1




WT766 - Type 3



WT768 - Type 2




WT780 - Type 1



WT764 - Type 3



WT761 - Type 3



WT763 - Type 1




WT762 - Type 1



WT767 - Type 3

WT Traditional Style Terrazzo Tile is available in 40 standard colors, using from 3/8" to 3/16" - minus aggregate.

WT Traditional Style Terrazzo Tile



WT782

Type 1

WT753

Type 1

WT787

Type 1

WT750


Type 1

WT785


Type 2




WT789 - Type 1



WT783 - Type 1




WT786 - Type 1




WT788 - Type 1



WT760 - Type 1



WT757 - Type 2



WT758 - Type 1



WT759 - Type 2

Our 40 colors are achieved through the mixing of unique matrix colors to enhance or blend with Wausau Tile stock aggregates.

800.388.8728 **9**

WT Traditional Style Terrazzo Tile

WT772
Type 1


WT770
Type 1

WT774
Type 1

WT754
Type 1

WT751
Type 1


WT784
Type 2



WT775 - Type 1



WT776 - Type 1



WT769 - Type 1



WT773 - Type 1




WT752 - Type 1



WT756 - Type 1



WT755 - Type 1




WT-771- Type 1

Wausau Tile Traditional Style Terrazzo Tile provides a full palette of standard colors with the option of custom colors that can be quoted upon request.


TG Recycled Terrazzo Glass Tile




TG-220 - Type A




TG-221 - Type A




TG-222 - Type A




TG-223 - Type A




TG-224 - Type B




TG-225 - Type A



TG-226 - Type A




TG-227 - Type B




TG-228 - Type A




TG-229 - Type A



TG-230 - Type A




TG-231 - Type B



TG-232 - Type B




TG-233 - Type A




TG-234 - Type A



TG-235 - Type A



TG-236 - Type A



TG-237 - Type B

In an effort to be environmentally conscious, Wausau Tile is introducing "glass" terrazzo. Our tile now utilizes all recycled glass products, 33% by weight.

800.388.8728 11

Matching Precast Stairs, Base, Copings



You can order the materials for your Thin Terrazzo floor as needed, saving storage space and the time it takes to handle the materials more than once.

The design potential with our colorful Thin Terrazzo Tile is unlimited. These beautiful floors will complement the rest of your facility, including matching Precast, base, stair treads, and wainscot.




Precast base




Base and wainscot

Oak Brook Library
Oak Brook, IL


Flat Base and Wainscot




S-31 Tread and Riser



S-30 Flat Tread



Modified S-50 Self-Supporting Tread




Installation Methods - 09300 Specification Tile-Set Method


Terrazzo tiles are manufactured with a high-polished surface and chamfered edges. The tiles are factory sealed. Terrazzo tile is installed following the Tile Council of America (TCA) specification for installation - F111, F112 and F113. Expansion control - EJ171 and crack isolation guidelines should also be followed. The substrate must have a 1/8" in ten foot tolerance to maintain a quality installation.

Our single layer thin terrazzo tile is provided unsealed. A grout release or seal coat must be applied to the tile prior to grouting. After the grout has dried, follow manufacturer's instructions for removal of the grout release. Clean the floor thoroughly with a neutral pH cleaner and apply the final floor seal with a product

F111 Cement Mortar, Cleavage Membrane



F112 Cement Mortar, Bonded



F113 Dry Set Mortar or Latex-Portland Cement Mortar, Bonded



Installation Methods - 09400 Specification Precast Terrazzo Flooring Ground-and-Polished Method


Wausau terrazzo tiles have a honed finish with square edges for use in the ground-and-polished method.

Terrazzo tile is installed following the Tile Council of America (TCA) specification for installation - F111, F112, and F113. Expansion control - EJ171 and crack isolation guidelines should also be followed. The substrate must have a 1/8" in ten foot tolerance to maintain a quality installation.


Square edge tiles are set with a 1/16" minus grout joint. Grouting procedures allow grout excess on the joint and tile. Tiles are then ground to remove all lippage, resulting in a smooth, monolithic finish with grout joints perfectly flush with the tile surface.

Clean the floor thoroughly with a neutral pH cleaner and apply the final floor seal with a product compatible with cement terrazzo, following the sealer manufacturer's

EJ171 Saw Cuts or Cold Joints



Crack Isolation Membrane



The beauty of Wausau Tile's Thin Terrazzo Tile speaks for itself. The hidden advantages are the cost savings in time and durability that will be enjoyed for years to come.

St. Augustine College
Chicago, IL

Terrazzo Flooring Product Summary

Style	Installation Method	Finish	Edges	Aggregate Size	Dimensions Tolerances	Weight Approx.	WT Colors	Custom Colors
Micro / WM	TGPM	• Honed (Not Factory Polished)	Square Edge	3/16" minus	11-13/16" x 11-13/16" x 1/2"	7 lbs.	14 WM	Yes
Accent / WA	TSM	• Factory Ground & Polished • Brushed	Chamfered Edge		11-13/16" x 11-13/16" x 5/8"	8.5 lbs.		Yes
					15-13/16" x 15-13/16" x 5/8"	13.5 lbs.		Yes
					23-13/16" x 23-13/16" x 7/8"	42 lbs.		Yes
Traditional / WT	TGPM	• Honed (Not Factory Polished)	Square Edge	3/8" - 3/16" minus	11-13/16" x 11-13/16" x 1/2"	7 lbs.	40	Yes
	TSM	• Factory Ground & Polished • Brushed	Chamfered Edge		11-13/16" x 11-13/16" x 5/8"	8.5 lbs.		Yes
					15-13/16" x 15-13/16" x 5/8"	13.5 lbs.		Yes
					23-13/16" x 23-13/16" x 7/8"	42 lbs.		Yes
Glass / TG	TSM	• Factory Ground & Polished	Chamfered Edge	3/8" - 1/4"	11-13/16" x 11-13/16" x 1/2"	7 lbs.	18	Yes
					11-13/16" x 11-13/16" x 5/8"	8.5 lbs.		Yes
					15-13/16" x 15-13/16" x 5/8"	13.5 lbs.		Yes
					23-13/16" x 23-13/16" x 7/8"	42 lbs.		Yes

WAUSAUTILE
America's One Source™



Since 1953

1
54402-1520
8
9.7456
utile.com

Mission Statement

Wausau Tile, founded in 1953, is dedicated to the principle of manufacturing the highest quality products, while providing the best customer service in our industry.

© 2006, Wausau Tile, Inc. All photos, text and actual products shown are the sole property of Wausau Tile, Inc., and may not be copied or duplicated without the express written permission of Wausau Tile, Inc.

06/2006

Terrazzo Flooring Physical Properties

Property	Value	Test Method	Property	Value	Test Method
Compressive Strength	8,000 psi Average	ASTM C140	Warpage (Along any edge)	+/- 1.5 %	—
Water Absorption	4.5%	ASTM C140	(Either diagonal)	+/- 1.5 %	—
Flexural Strength	950 psi Average	ASTM C293	Static Coefficient of Friction	Dry Wet	ASTM C1028
Wedging	<1%	—	Polished	0.6 0.5	

PRSRT STD
U.S. POSTAGE
PAID
PERMIT 182
WAUSAU WI