

DESCRIPTION

- Metal construction with chrome plated, LifeShine® stainless, oil rubbed bronze, nickel or wrought iron finish
- 1/2" IPS connections will accept standard ball nose connection for 3/8" tubing
- Includes optional hot and cold temperature indicators
- Includes matching finish side spray with Hydrolock® quick connect system
- Hydrolock® quick connect installation

OPERATION

- Lever style handles
- Rotate hot side handle counterclockwise to open and clockwise to close
- Rotate cold side handle clockwise to open and counterclockwise to close

FLOW

- Aerator is limited to 2.2 gpm max. (8.3 L/min)

CARTRIDGE


- 1224 cartridge design with nonmetallic/nonferrous and stainless steel materials

STANDARDS


- Third party certified to CSA B125, ASME A112.18.1M, ANSI A117.1 and all applicable requirements referenced therein
- Certified to ANSI/NSF 61/9
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



Waterhill™
Two-Handle Kitchen Faucet
Models: S712, S712SL, S712ORB,
S712NL, S712WR



NOTE: MINIMUM DIA. HOLES FOR INSTALLATION

- Spout = 1-1/4" (32mm)
- Handle Valves = 1-1/8" (29mm)
- Side Spray = 1" (25mm)

QUICK CONNECT HOSE ASSEMBLY

CRITICAL DIMENSIONS

(DO NOT SCALE)