

O SERIES

© 2005 Antoine Proulx



LT-98P PENDANT LIGHT FIXTURE (RECTANGLE, shown above)

- 18"ø x 10"h, 25 lbs. (accepts two 60 Watt incandescent light bulbs)
- 18"w x 18"d x 10"h, 25 lbs. (accepts two 60 Watt incandescent light bulbs)
- 24"ø x 12"h, 45 lbs. (accepts four 60 Watt incandescent light bulbs)
- 24"w x 24"d x 12"h, 55 lbs. (accepts four 60 Watt incandescent light bulbs)
- 30"ø x 15"h, 50 lbs. (accepts four 60 Watt incandescent light bulbs)
- 30"w x 30"d x 15"h, 50 lbs. (accepts four 60 Watt incandescent light bulbs)
- 44"ø x 20"h, 75 lbs. (accepts four 60 Watt incandescent light bulbs)
- 44"l x 16"w x 15"h, 75 lbs. (accepts four 60 Watt incandescent light bulbs)
- 54"ø x 20"h, 95 lbs. (accepts six 60 Watt incandescent light bulbs)

Shade is steel (with baked-on epoxy finish) with sandblasted acrylic.

Top of shade is enclosed in steel with laser-cut pattern to allow heat to escape.

Stem (or drop) is four .75" square steel tubing rods (with baked-on epoxy finish).

Bottom of shade is enclosed with four (or 6 on 54"ø) pie-shaped pieces of sandblasted acrylic.

Canopy is cold-rolled steel. 18" chandeliers: 6"w x 6"d x 1.75"h; 54"ø chandeliers: 12"w x 12"d x 1.75"h.

Canopy on all other chandeliers is 9"w x 9"d x 1.75"h.

Cannot be supported by a j-box only. Attachment to rafters is necessary. Mounting bracket provided.

Must specify length of fixture inclusive of canopy, stem, and shade (i.e. from ceiling to bottom of shade).

