

Job Name: Contact:

Fixture Type: Part Number:

BLING II DIAMOND SCONCE















Description:

The Bling II wall sconce may be mounted as an up-light or a down-light. The wall sconce may be mounted as a square or at an 45 degree angle to create a diamond shape. The metal canopy and stem is available in bronze. A 75W dimmable electronic transformer is included on the mounting plate.

Part Numbers:

101174bz bronze, amber glass 101174ch chrome, amber glass 101174mc matte chrome, amber glass 101179bz bronze, white glass 101179ch chrome, white glass 101179mc matte chrome, white glass 101843bz bronze, black glass 101843ch chrome, black glass 101843mc matte chrome, black glass 101844bz bronze, gold glass 101844ch chrome, gold glass 101844mc matte chrome, gold glass 101845bz bronze, silver glass 101845ch chrome, silver glass 101845mc matte chrome, silver glass

Technical Specs:

120V AC, 50/60Hz input
11.7V AC output
50VA, 49W for 1(maximum 50 Watt lamp)
GY6.35 socket
Suitable for dry locations only
Mount to 3 1/2" - 4" round J-box
Short circuit protection
Overload protection
Thermal protection
Dimmable

 Bruck Lighting System, Inc.
 15774 Gateway Circle
 Tustin, CA 92780
 p:714.259.9959
 f:714.259.9969
 16 Jul 2010