


INSTALLATION AND WIRING DIAGRAM

USA

INDIVIDUAL

HAVANA II LED DOWN

ART. NO. 135 700ch/MP2 chrome
135 700mc/MP2 matte chrome



IMPORTANT SAFETY INSTRUCTIONS



1. Save these instructions and refer to them when additions to or changes to the fixture are made.
2. THIS PRODUCT MUST BE INSTALLED BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED, IN ACCORDANCE WITH THE APPLICABLE NEC CODE.
3. Do not install this fixture in damp or wet locations.
4. CAUTION - Do not install any fixture assembly closer than 6 inches from any curtain, or similar combustible material.
5. Turn off power prior to any work on the fixture.
6. Warranty is void in case of unauthorized modifications and/ or improper use.
7. No thru wiring.

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE FIXTURE

Contents of Delivery:

HAVANA II LED DOWN - qty. (1)

NOTE

The 2" surface mount canopy is designed for a ceiling thickness between 1-1/16" and 3/16".

Step 1.

- Drill a 2-1/4" hole in the mounting surface.
- Adjust the cable length of the fixture by adjusting the strain relief prior to mounting the J-box.
- Coil excess cable and tuck inside the J-box.

Step 2.

- Slide the j-box (D) into the mounting surface (make sure the side brackets (G) are not extended outwards). When possible, place support ring (E) over J-box. Tighten the mounting screws (H) to extend the side brackets and hold the j-box in place. DO NOT overtighten the screws; the side brackets may cut through the mounting surface.

Step 3.

- Pull the line voltage wires (A) and ground wire (B) through the back plate (C). Use wire nuts to connect the wires to the black, white, and green wires from the transformer. Attach the back plate (C) to the j-box (D) with screws.

Step 4.

- Place the magnetic cover-plate (F) over the j-box (D) to complete the installation.

