

**Quality: IRISA**

**Kollektion: Ulf Moritz by Vorwerk**

**Description of good:** tufted 1/5" loop, uni      **Pile utility coat:** 80% wool / 20% polyamide  
**Coating:** Textile back made of PP grid canvas



CE

Vorwerk & Co. Teppichwerke  
GmbH & Co. KG  
Kuhlmannstrasse 11  
D – 31785 Hameln

EN 14041: 2004




---

EN 1307



**strain value**



**comfort value**

Partition / 10 cm	ca.	20	Pile inset weight g/m <sup>2</sup>	ca.	1200
Prick rate / 10 cm	ca.	39	Total weight g/m <sup>2</sup>	ca.	2700
Nap rate in dm <sup>2</sup>	ca.	780	Pile utility coat weight g/m <sup>2</sup>	ca.	870
Pile thickness in mm	ca.	5,0	Pile raw density g/cm <sup>3</sup>	ca.	0,170
Total thickness in mm	ca.	8,0			

**Confalgrative behavior**      **DIN EN 13501-1**      E<sub>fl</sub>

<b>Resistance to water</b>	DIN EN ISO 105-E 01 Change of colour	mind. Note 4
<b>Resistance to light</b>	DIN EN ISO 105-B 02	mind. Note 5
<b>Resistance to friction</b>	DIN EN ISO 105-X 12	mind. Note 4

In order to avoid change or measure, we recommend a fixed laying (glue with dispersion adhesive). Laying manual: see current maintenance and laying manual. Because of permanent further development and improvement of quality any change of technical data is reserved.