

**Quality:** PURITA **Collektion:** Ulf Moritz by Vorwerk

**Description of good:** tufted 1/8" loop **Pile utility coat:** 100 % new wool  
**Coating:** Textile back made of PP grid canvas





**Vorwerk & Co. Teppichwerke  
GmbH & Co. KG  
Kuhlmannstrasse 11  
D – 31785 Hameln**

**EN 14041: 2004**




---

**EN 1307**



**strain value**



**comfort value**

Partition / 10 cm	ca.	31	Pile inset weight g/m <sup>2</sup>	ca.	1900
Prick rate / 10 cm	ca.	27	Total weight g/m <sup>2</sup>	ca.	3000
Nap rate in dm <sup>2</sup>	ca.	837	Pile utility coat weight g/m <sup>2</sup>	ca.	1470
Pile thickness in mm	ca.	10,0	Pile raw density g/cm <sup>3</sup>	ca.	0,145
Total thickness in mm	ca.	12,6			

**Confalgrative behavior**      **DIN EN 13501-1**      E<sub>fl</sub>

**Resistance to water**      DIN EN ISO 105-E 01 Change of colour      mind. Note 4  
**Resistance to light**      DIN EN ISO 105-B 02      mind. Note 5  
**Resistance to friction**      DIN EN ISO 105-X 12      mind. Note 4

In order to avoid change or measure, we recommend a fixed laying (glue with dispersion adhesive). Laying manual: see current maintenance and laying manual. Because of permanent further development and improvement of quality any change of technical data is reserved.