

# Classic Ceiling

performance architectural lighting



RIC1000  
Polished Brass

16"

24"

32"

42"

Traditional Trim

Stepped Trim

Bullnose Trim



RIC1010  
Brushed Aluminum





RIC1020  
Painted-Pearl White




# Classic Ceiling

RENAISSANCE




# 16"






# 24"



# 32"



# 42"



## Specifications:

- Trim rings are spun from .063" thick base material (brass or aluminum) or 18 gauge steel (plated or painted).
- Chassis is formed from 18 gauge cold-rolled steel.
- Formed acrylic bowl with a minimum wall thickness of .118". Opal finish is standard.
- Integral fluorescent ballasts are HPF electronic with low harmonic distortion.
- Ballasts are thermally protected and have Class "A" sound rating.
- Backplate attaches to standard 4" octagonal junction box.
- UL listed (US and Canada) for damp locations. (Not recommended for exterior use.)

Design modification rights reserved.




Sample model number: **RIC1000 - 2F26 - 120 - BAL - HP02**

Select Style	Select any Lamping (indirect/bowl illumination)	Lamping Detail (indirect - bowl illumination)	Optical Pkg.	Photometry	Select Voltage	Select Finish	Select Options
16" <b>RIC1000</b> <b>RIC1010</b> <b>RIC1020</b>	<b>2F13<sup>1</sup></b>	(2) CFQ13W/G24q	A	NA	<b>120</b> <b>277</b>	<b>PT</b> Painted. (Include Paint Number.) <b>PBR</b> Polished solid brass <b>BBR</b> Brushed solid brass <b>ABR</b> Antique solid brass <b>CPBR</b> Chrome plated polished brass <b>BAL</b> Brushed aluminum <b>ABST</b> Antique brass over steel <b>BBST</b> Brushed brass over steel <b>CPST</b> Polished chrome over steel <b>PBST</b> Polished brass over steel  <i>See Finish Selection Guide, pages 268-269.</i>	<b>SP</b> Spacer canopy (Not available for RIC1004, 1006, 1014, 1016 1024 and 1026.) <b>F</b> Fuse option <b>EMI<sup>1</sup></b> Emergency ballast(s) integral (Requires SP-Spacer canopy) <b>EMR</b> Emergency ballast(s) remote <b>SBA</b> Sandblasted acrylic <b>HP01</b> Silver hand-painted acrylic <b>HP02</b> Beige hand-painted acrylic <b>HP03</b> Amber hand-painted acrylic <b>FIN</b> Finial option
	<b>2F26<sup>1</sup></b>	(2) CFQ26W/G24q	A	NA			
	<b>1N60</b>	60W A19 INC	B	E433-35			
	<b>1F22<sup>1</sup></b>	22W CIRC T5	C	NA			
24" <b>RIC1002</b> <b>RIC1012</b> <b>RIC1022</b>	<b>3N60</b>	(3) 60W A19 INC	D	NA			
	<b>1N150</b>	150W A21 INC	E	NA			
	<b>2F26<sup>1</sup></b>	(2) CFQ26W/G24q	F	NA			
	<b>2F39<sup>1</sup></b>	(2) FT39W/2G11	F	NA			
32" <b>RIC1004</b> <b>RIC1014</b> <b>RIC1024</b>	<b>3F39</b>	(3) FT39W/2G11	G	NA			
	<b>3F39DM</b>	(3) FT39W/2G11	G	NA			
	<b>4F39</b>	(4) FT39W/2G11	H	NA			
	<b>3N100</b>	(3) 100W A19 INC	D	NA			
42" <b>RIC1006</b> <b>RIC1016</b> <b>RIC1026</b>	<b>4F39</b>	(4) FT39W/2G11	H	NA			
	<b>3N150</b>	(3) 150W A21 INC	D	NA			

**DM** = Dimming ballast(s) provided

<sup>1</sup>Denotes lamping options available with **EMI** (Requires **SP**-Spacer canopy)

*If Photometry is not available, consult factory for further details.*

*For further detail on options, see Technical Notes on page 264.*

### OPTICAL PACKAGES

