

16"

24"


32"

Specifications:


- Trim rings are spun from .063" thick base material (brass or aluminum) or 18 gauge steel (plated or painted).
- Chassis is formed from 18 gauge cold-rolled steel.
- Formed acrylic bowl with a minimum wall thickness of .118". Opal finish is standard.
- Integral fluorescent ballasts are HPF electronic with low harmonic distortion.
- Ballasts are thermally protected and have Class "A" sound rating.
- Backplate attaches to standard 4" octagonal junction box.
- UL listed (US and Canada) for damp locations. (Not recommended for exterior use.)

Design modification rights reserved.


Stepped Trim



RIC1040



RIC1042



RIC1044



RIC1044

Brushed Aluminum

Sample model number: **RIC1044 - 3F39 - 120 - BAL - HP02**

Select Style	Select any Lamping (bowl illumination)	Lamping Detail (bowl illumination)	Optical Pkg. Photometry	Select Voltage	Select Finish	Select Options
16" RIC1040	2F13	(2) CFQ13W/G24q	A NA	120 277	PT Painted. (Include Paint Number.) PBR Polished solid brass BBR Brushed solid brass ABR Antique solid brass CPBR Chrome plated polished brass BAL Brushed aluminum ABST Antique brass over steel BBST Brushed brass over steel CPST Polished chrome over steel PBST Polished brass over steel	SP Spacer canopy (Not available for RIC1044.) F Fuse option (M and F) EMI ¹ Emergency ballast(s) integral EMR Emergency ballast(s) remote SBA Sandblasted acrylic HP01 Silver hand-painted acrylic HP02 Beige hand-painted acrylic HP03 Amber hand-painted acrylic FIN Finial option
	2F26	(2) CFQ26W/G24q	A NA			
	1N60	60W A19 INC	B E433-35			
	1F22	22W CIRC T5	C NA			
24" RIC1042	3N60	(3) 60W A19 INC	D NA	<i>See Finish Selection Guide, pages 268-269.</i>	 Stepped	<i>For further detail on options, see Technical Notes on page 264.</i>
	1N150	150W A21 INC	B NA			
	2F26 ¹	(2) CFQ26W/G24q	E NA			
	2F39 ¹	(2) FT39W/2G11	E NA			
32" RIC1044	1F40	40W CIRC T5	C NA			
	3F39	(3) FT39W/2G11	F NA			
	3F39DM	(3) FT39W/2G11	F NA			
	4F39	(4) FT39W/2G11	G NA			
	3N100	(3) 100W A19 INC	H NA			

DM = Dimming ballast(s) provided

If Photometry is not available, consult factory for further details.

¹Denotes lamping options available with EMI (Requires SP-Spacer canopy)

OPTICAL PACKAGES

