

Shallow Arm Sconce & Ceiling



RIW1180
Brushed Aluminum

16" 24" 32"

Stepped Trim



RIC1080
Brushed Aluminum

Shallow Ceiling

RENAISSANCE

16"

24"




32"

Specifications:


- Trim rings are spun from .063" thick base material (brass or aluminum) or 18 gauge steel (plated or painted).
- Chassis is formed from 18 gauge cold-rolled steel.
- Formed acrylic bowl with a minimum wall thickness of .118". Opal finish is standard.
- Integral fluorescent ballasts are HPF electronic with low harmonic distortion.
- Ballasts are thermally protected and have Class "A" sound rating.
- Backplate attaches to standard 4" octagonal junction box.
- UL listed (US and Canada) for damp locations. (Not recommended for exterior use.)

Design modification rights reserved.

Stepped Trim



Sample model number: **RIC1084 - 1F40/1F22 - 120 - BAL - HP02**

	Select Style	Select Lamping (bowl illumination)	Lamping Detail (bowl illumination)	Optical Pkg.	Photometry	Select Voltage	Select Finish	Select Options
16"	RIC1080	1F22	22W CIRC T5	A	NA	120 277	PT_ Painted. (Include Paint Number.) PBR Polished solid brass BBR Brushed solid brass ABR Antique solid brass CPBR Chrome plated polished brass BAL Brushed aluminum ABST Antique brass over steel BBST Brushed brass over steel CPST Polished chrome over steel PBST Polished brass over steel <i>See Finish Selection Guide, pages 268-269.</i>	SP Spacer canopy. (Not available for RIC1084.) F Fuse option EMR Emergency ballast(s) remote SBA Sandblasted acrylic HP01 Silver hand-painted acrylic HP02 Beige hand-painted acrylic HP03 Amber hand-painted acrylic FIN Finial option  Stepped <i>For further detail on options, see Technical Notes on page 264.</i>
24"	RIC1082	1F40	40W CIRC T5	A	NA			
32"	RIC1084	1F40 / 1F22	40W CIRC T5 - 22W CIRC T5	A	NA			

DM = Dimming ballast(s) provided

If Photometry is not available, consult factory for further details.

OPTICAL PACKAGES

A

