

Swept Ceiling




RENAISSANCE

16"




24"

32"

Traditional Trim



Bullnose Trim



Specifications:

- Trim rings are spun from .063" thick base material (brass or aluminum) or 18 gauge steel (plated or painted).
- Chassis is formed from 18 gauge cold-rolled steel.
- Formed acrylic bowl with a minimum wall thickness of .118". Opal finish is standard.
- Integral fluorescent ballasts are HPF electronic with low harmonic distortion.
- Ballasts are thermally protected and have Class "A" sound rating.
- Backplate attaches to standard 4" octagonal junction box.
- UL listed (US and Canada) for damp locations. (Not recommended for exterior use.)



RIC1050
Polished Brass



RIC1060
Polished Brass

Sample model number: **RIC1050 - 1F22 - 120 - BAL - HP02**

	Select Style	Select Lamping (bowl illumination)	Lamping Detail (bowl illumination)	Optical Pkg.	Photometry	Select Voltage	Select Finish	Select Options
16"	RIC1050 RIC1060	1F22	22W CIRC T-5	A	NA	120 277	PT_ Painted. (Include Paint Number.) PBR Polished solid brass BBR Brushed solid brass ABR Antique solid brass CPBR Chrome plated polished brass BAL Brushed aluminum ABST Antique brass over steel BBST Brushed brass over steel CPST Polished chrome over steel PBST Polished brass over steel	SP Spacer canopy. (Not available for RIC1054 and 1064.) F Fuse option EMR Emergency ballast(s) remote SBA Sandblasted acrylic HP01 Silver hand-painted acrylic HP02 Beige hand-painted acrylic HP03 Amber hand-painted acrylic FIN Finial option
24"	RIC1052 RIC1062	1F40	40W CIRC T5	A	NA			
32"	RIC1054 RIC1064	1F40 / 1F22	40W CIRC T5 - 22W CIRC T5	A	NA			

If Photometry is not available, consult factory for further details.

See Finish Selection Guide, pages 268-269.

Traditional
Bullnose

For further detail on options,
see Technical Notes on page 264.

OPTICAL PACKAGES

A

