



Exterior Wall Mount

Specifications:



- **Extruded** - Extruded .156" aluminum housing.
- H.I.D. luminaires have a cast aluminum cover with gasketing and impact and heat-resistant, tempered glass lens.
- Cast aluminum end caps and flush mounted fasteners.
- Housing is field adjustable for application specific aiming and can be mechanically locked in the desired position.
- H.I.D. luminaires utilize a segmented, 95% reflective, specular clear, aluminum reflector.
- Yoke is die-formed from 14 gauge stainless steel. Luminaires over 27" in length have a two-piece yoke assembly.
- Hub and Horizontal Stem mountings utilize a cast aluminum canopies. Horizontal Stem mount units include 1 1/2" dia. stainless steel stems and canopies. Hub mount supplied with round canopies.
- Assembly includes a steel cover to fit over a standard 4" junction box.
- Flexible weatherproof power cord with watertight fittings. Black standard.
- Housings, endcaps, brackets and cover plates painted to match. Standard finish is thermoset polyester powder coat. All metal surfaces go through a 5-stage pretreatment process prior to powder coat application.
- H.I.D. remote ballasts are encased and potted, magnetic CWA-HPF design (120/277 volt operation). Ballasts are thermally protected and have a Class "B" sound rating for 175W. Class "C" rating for 250W and 400W.
- Power Tray™ integral ballast is a multi-tap 120/277 volt, open core and coil magnetic ballast with all components installed on a tray, pre-wired with quick-connect plugs for ease of installation and maintenance. Ballast is thermally protected and has a Class "C" sound rating.
- UL listed (U.S. and Canada) for wet locations.

Assistance Available: Please see our website, or call 262-242-1420 for more specific product information, applications assistance or modification requests.



Yoke





Hub



Horizontal Stem




Power Tray



ECHO 9.0

Remote or Integral Ballast

| FT | PW | VG | Lamp Wattage Range | Lamp |
|----|----|----|--------------------|------|
| | | | | FL |
| | | | 175-800W | MH |
| | | | 500W | TH |



Remote Ballast

| | Mounting | | Housing | Lamping Detail | |
|----------|-------------|-------------|----------|-------------------------------------|-------------------------------------|
| | | | | | |
| 16" | EEW 3000 | Yoke | Extruded | 1M175 | (1) 175W ED17 MH - Medium |
| | EEW 3006 | Hub | | 1M250 | (1) 250W ET18 MH - Mogul |
| | EEW 3012 | Horiz. Stem | | 1M250PS | (1) 250W T15 Pulse Start MH - Mogul |
| 27.5" | | | | 1M400 | (1) 400W ET18 MH - Mogul |
| | | | | 1M400PS | (1) 400W T15 Pulse Start MH - Mogul |
| | | | | 2T250 ² | (2) 250W T4 DC BAY QTZ |
| | EEW 3024 | Yoke | Extruded | 2M250 | (2) 250W ET18 MH - Mogul |
| | EEW 3030 | Hub | | 2M250PS | (2) 250W T15 Pulse Start MH - Mogul |
| EEW 3036 | Horiz. Stem | 2M400 | | (2) 400W ET18 MH - Mogul | |
| | | 2M400PS | | (2) 400W T15 Pulse Start MH - Mogul | |

| | |
|-----------|---------------|
| FT | Forward Throw |
| PW | Plane Wash |

120
277

PT Painted. (Include Paint Number)

See SPI Finish Selection Guide on pages 168-169.

Other voltages/frequencies are available. For additional details and options, see Technical Notes on page 166 or consult factory for information.

| | |
|------------|--|
| F | Fuse. (metal halide lamping) |
| RPI | Interior remote ballast support tray. (metal halide lamping) |
| CS | Cut-off Shield. |
| RBE | Remote wet location ballast kit (metal halide lamping) |

For further details on Options, see Technical Notes on page 165.

Integral Ballast

| | Mounting | | Housing | Lamping Detail | |
|-------|----------|------------|----------|-------------------------------------|-------------------------------------|
| | | | | | |
| 16" | EEW 3134 | Power Tray | Extruded | 1M175 | (1) 175W ED17 MH - Medium |
| | | | | 1M250 | (1) 250W ET18 MH - Mogul |
| | | | | 1M250PS | (1) 250W T15 Pulse Start MH - Mogul |
| | | | | 1M400 | (1) 400W ET18 MH - Mogul |
| 27.5" | | | | 1M400PS | (1) 400W T15 Pulse Start MH - Mogul |
| | EEW 3140 | Power Tray | Extruded | 2M250 | (2) 250W ET18 MH - Mogul |
| | | | | 2M250PS | (2) 250W T15 Pulse Start MH - Mogul |
| | | | | 2M400 | (2) 400W ET18 MH - Mogul |
| | | 2M400PS | | (2) 400W T15 Pulse Start MH - Mogul | |

² 120 volt only.
For additional lamping details and options, see Technical Notes on pages 160-161.

Reflections
Wall
Ceiling
Pendant

3.5
Wall
Ceiling
Pendant

5.0
Wall
Ceiling
Pendant
Pier
Cove
MRI
Shapes

6.0
Wall
Ceiling
Pendant
Pier
Cove
MRI

9.0
Wall
Ceiling
Pendant
Pier
Cove
MRI
Shapes

16.5
Wall
Pier
Pendant

Exterior

Lightruss