



Interior Wall Mount



Yoke





Specifications:

- **Solid** - Roll-formed 20 gauge steel housing.
- **Perforated** - Roll-formed, perforated 20 gauge steel housing.
- Cast aluminum end caps with flush-mounted fasteners.
- Housing is field adjustable for application specific aiming and can be mechanically locked in the desired position.
- H.I.D. and Tungsten Halogen luminaires utilize a segmented, 95% reflective, specular clear, aluminum reflector. Impact and heat-resistant, tempered pattern 62 glass lens.
- Yoke bracket is die-formed from 14 gauge steel.
- Cantilever Arm mount utilizes a yoke bracket with a 1" dia. steel arm.
- Formed steel cover to fit over a standard 4" junction box.
- Power Tray™ is a two-piece ballast and yoke assembly, die-formed from 18 gauge steel for ballast box and 14 gauge steel for mounting yoke.
- Housing, endcaps, brackets, cover plates and stems painted to match. Standard finish is thermoset polyester powder coat. All metal surfaces go through a 5-stage pretreatment process prior to powder coat application.
- H.I.D. remote ballasts are encased and potted, magnetic CWA-HPF design (120/277 volt operation). Ballasts are thermally protected and have a Class "B" sound rating.
- Power Tray™ integral ballast is a dual-tap 120/277 volt, open core and coil magnetic ballast with all components installed on a tray, pre-wired with quick-connect plugs for ease of installation and maintenance. Ballast is thermally protected and has a Class "C" sound rating.
- UL listed (U.S. and Canada) for damp locations. (Not for exterior use.)

Cantilever Arm



Power Tray



Assistance Available: Please see our website, or call 262-242-1420 for more specific product information, applications assistance or modification requests.

ECHO 5.0

Remote or Integral Ballast

FT	PW	VG	Lamp Wattage Range	Lamp
				FL
<input type="checkbox"/>			39-150W	MH
<input type="checkbox"/>			150-250W	TH

SELECT STYLE

SELECT LAMPING

SELECT OPTICAL PACKAGE

SELECT VOLTAGE

SELECT FINISH

SELECT OPTIONS

Remote Ballast

	Mounting	Housing
EIW 1500	Yoke	Perforated
EIW 1502	Yoke	Solid
EIW 1510	Cant. Arm	Perforated
EIW 1512	Cant. Arm	Solid

	Lamping Detail
1M39	(1) 39W T6 CMH/G12
1M70	(1) 70W T6 CMH/G12
1M150	(1) 150W T6 CMH/G12
1T150 ²	(1) 150W T4 DC BAY QTZ
1T250 ²	(1) 250W T4 DC BAY QTZ

FT Forward Throw

120
277

PT_ Painted. (Include Paint Number)

See SPI Finish Selection Guide on pages 168-169.

Other voltages/frequencies are available. For additional details and options, see Technical Notes on page 166 or consult factory for information.

CS Cut-off Shield.

RPI Remote ballast support tray. (metal halide lamping)

F Fuse. (metal halide lamping)

For further details on Options, see Technical Notes on page 164.

Integral Ballast

	Mounting	Housing
EIW 1516	Yoke	Perforated
EIW 1518	Yoke	Solid

	Lamping Detail
1M39	(1) 39W T6 CMH/G12
1M70	(1) 70W T6 CMH/G12
1M150	(1) 150W T6 CMH/G12

² 120 volt only
For additional lamping details and options, see Technical Notes on pages 160-161.

- Reflections
- Wall
- Ceiling
- Pendant
- 3.5
- Wall
- Ceiling
- Pendant
- 5.0
- Wall
- Ceiling
- Pendant
- Pier
- Cove
- MRI
- Shapes
- 6.0
- Wall
- Ceiling
- Pendant
- Pier
- Cove
- MRI
- 9.0
- Wall
- Ceiling
- Pendant
- Pier
- Cove
- MRI
- Shapes
- 16.5
- Wall
- Pier
- Pendant
- Exterior
- Lightruss