



Interior Ceiling Mount



Semi-recessed





Specifications:

- **Solid** - Roll-formed 20 gauge steel housing.
- **Perforated** - Roll-formed, perforated 20 gauge steel housing.
- Cast aluminum end caps with flush-mounted fasteners.
- Housing is field adjustable for application specific aiming and can be mechanically locked in the desired position.
- Recessed housing can be mounted in ceiling.
- Recessed housing has universal mounting brackets that can accept 1/2" EMT, lathing channels or hanger brackets.
- Yoke bracket is die-formed from 14 gauge steel.
- Formed steel cover is provided to fit over a standard 4" junction box.
- The Ceiling Mount Kit utilizes a yoke bracket with a cover plate that mounts to a standard 4" junction box. Allows for 356° adjustability.
- H.I.D. and Tungsten Halogen luminaires utilize a segmented, 95% reflective, specular clear, aluminum reflector. Impact and heat-resistant, tempered pattern 62 glass lens.
- H.I.D. ballasts are remote, encased and potted, magnetic CWA-HPF design (120/277 volt operation). Ballasts are thermally protected and have a Class "B" sound rating.
- Housing, endcaps, brackets, and cover plates painted to match. Standard finish is thermoset polyester powder coat. All metal surfaces go through a 5-stage pretreatment process prior to powder coat application.
- UL listed (U.S. and Canada) for damp locations. (Not for exterior use.)

Yoke



Ceiling Mount Kit




Assistance Available: Please see our website, or call 262-242-1420 for more specific product information, applications assistance or modification requests.

ECHO 5.0

Remote Ballast

FT	PW	VG	Lamp Wattage Range	Lamp
				FL
<input type="checkbox"/>			39-150W	MH
<input type="checkbox"/>			150-250W	TH



SEMI-RECESSED

	Mounting	Housing
EIS 1500	Semi-Rec.	Perforated
EIS 1502	Semi-Rec.	Solid

Lamping Detail

1M39	(1) 39W T6 CMH/G12
1M70	(1) 70W T6 CMH/G12
1M150	(1) 150W T6 CMH/G12
1T150²	(1) 150W T4 DC BAY QTZ
1T250²	(1) 250W T4 DC BAY QTZ

FT Forward Throw

120
277

PT_ Painted. (Include Paint Number)

See SPI Finish Selection Guide on pages 168-169.

Other voltages/frequencies are available. For additional details and options, see Technical Notes on page 166 or consult factory for information.

CS	Cut-off Shield.
RPI	Remote ballast support tray. (metal halide lampping)
F	Fuse. (metal halide lampping)

For further details on Options, see Technical Notes on page 164.

CEILING MOUNT

	Mounting	Housing
EIC 1500	Yoke	Perforated
EIC 1502	Yoke	Solid
EIC 1510	CM Kit	Perforated
EIC 1512	CM Kit	Solid

Lamping Detail

1M39	(1) 39W T6 CMH/G12
1M70	(1) 70W T6 CMH/G12
1M150	(1) 150W T6 CMH/G12
1T150²	(1) 150W T4 DC BAY QTZ
1T250²	(1) 250W T4 DC BAY QTZ

² 120 volt only.
For additional lamping details and options, see Technical Notes on pages 160-161.

- Reflections
- Wall
- Ceiling
- Pendant
- 3.5
- Wall
- Ceiling
- Pendant
- 5.0
- Wall
- Ceiling
- Pendant
- Pier
- Cove
- MRI
- Shapes
- 6.0
- Wall
- Ceiling
- Pendant
- Pier
- Cove
- MRI
- 9.0
- Wall
- Ceiling
- Pendant
- Pier
- Cove
- MRI
- Shapes
- 16.5
- Wall
- Pier
- Pendant
- Exterior
- Lightruss