

Arches Table Specifications:

Top Construction:

Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Tables 66" and longer include steel support to prevent sagging. Standard edges are T-mold and 3mm PVC. Other edges available*:

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

**Custom edges may not be available with all shapes and sizes.
See www.SpecialT.net → product page → edge tab for edge offering.*



Base Construction:

Bolted/welded
 Base height: 27.75"
 Columns: 2" diameter, 14 gauge steel
 Arched feet: 2" diameter, 14 gauge steel
 Welded Mounting Plate: 5" x 8" x 7/32" steel
 Levelers: 1-3/8" diameter, 1/2" long stud
 Finish: powder coat or optional polished chrome
 Load capacity: 330 lbs. (200kg) vertical load rating per base

Options:

- Casters
- T or C leg
- Folding
- Bar height
- Adjustable height
- Modesty panels
- Grommets
- Wire management
- Table joiners



For easy installation, tops are pre-drilled.
 The base positioning is as following:

36" - 48"	3.5" from the edge to column center
54"	4" from the edge to column center
60" - 72"	6" from the edge to column center
84"	12" from the edge to column center
96"	12" from the edge to column center