

## Convertible Table Specifications:

## **Top Construction:**

Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Tables 66" and longer include steel support to prevent sagging. Standard edges are T-mold and 3mm PVC. Other edges available\*:

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

\*Custom edges may not be available with all shapes and sizes. See www.SpecialT.net → product page → edge tab for edge offerings.

## **Base Construction:**

Bolted/welded Base height: 27.75"

Columns: 1.5" diameter, 14 gauge steel

Casters: 3" skate wheel casters

Finish: powder coat

Mounting beam: heavy duty tubular steel with single point positive locking release mechanism

(3) 5" x 8" x 7/32" steel hinges

## Optons:

- Bell glides
- Integra folding modesty panel
- Grommets
- Wire management
- Table joiners

For easy installation, tops are pre-drilled. Legs position is 5" from the edge to the center of the column.





One point positive locking release mechanism



Straight-on Nesting