



## Interior Cove Mount

### Cove



### Specifications:

- The housing is die-formed from 20 gauge perforated steel and can be mounted to horizontal or vertical surfaces.
- Pre-wired with 18" long, 1/2" O.D. flexible metal conduit, and insulated wire leads extend 6".
- Housing is field adjustable for application specific aiming and can be mechanically locked in the desired position.
- H.I.D. luminaries utilize a segmented, 95% reflective, specular clear, aluminum reflector. Impact and heat-resistant, tempered glass lens.
- H.I.D. ballasts are remote, encased and potted, magnetic CWA-HPF design (120/277 volt operation). Ballasts are thermally protected and have a Class "B" sound rating for 175W and a class "C" sound rating for 250W and 400W.
- The housing and brackets are painted to match. Standard finish is thermoset polyester powder coat. All metal surfaces go through a 5-stage pretreatment process prior to powder coat application.
- UL listed (U.S. and Canada) for damp locations. (Not for exterior use.)

Assistance Available: Please see our website, or call 262-242-1420 for more specific product information, applications assistance or modification requests.

FT	PW	VG	Lamp Wattage Range	Lamp
				FL
			175-400W	MH
				TH

**SELECT STYLE**

Mounting: **EIV 3002**

Housing: Cove, Perforated

**SELECT LAMPING**

Lamping Detail

<b>1M175</b>	(1) 175W ED17 MH - Medium
<b>1M250</b>	(1) 250W ET18 MH - Mogul
<b>1M400</b>	(1) 400W ET18 MH - Mogul
<b>1M250PS</b>	(1) 250W T15 Pulse Start MH - Mogul
<b>1M400PS</b>	(1) 400W T15 Pulse Start MH - Mogul

For additional lamping details and options, see Technical Notes on pages 160-161.

Dimming ballast provides from 100% to 10% lumen output, <20%THD and start temperature of 10° C.

**SELECT OPTICAL PACKAGE**

**FT** Forward Throw

**SELECT VOLTAGE**

**120**  
**277**

Other voltages/frequencies are available. For additional details and options, see Technical Notes on page 166 or consult factory for information.

**SELECT FINISH**

**PT\_** Painted. (Include Paint Number)

See SPI Finish Selection Guide on pages 168-169.

**SELECT OPTIONS**

**F** Fuse.

**Q** Standby Quartz Lamping.

For further details on Options, see Technical Notes on page 165.

- Reflections
- Wall
- Ceiling
- Pendant
- 3.5
- Wall
- Ceiling
- Pendant
- 5.0
- Wall
- Ceiling
- Pendant
- Pier
- Cove
- MRI
- Shapes
- 6.0
- Wall
- Ceiling
- Pendant
- Pier
- Cove
- MRI
- 9.0
- Wall
- Ceiling
- Pendant
- Pier
- Cove
- MRI
- Shapes
- 16.5
- Wall
- Pier
- Pendant
- Exterior
- Lightruss