

Kingston Table Specifications:

Top Construction:

Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Tables 66" and longer include steel support to prevent sagging. Standard edges are T-mold and 3mm PVC. Other edges available*:

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

**Custom edges may not be available with all shapes and sizes.
See www.SpecialT.net → product page → edge tab for edge offerings.*



Base Construction:

Bolted/welded
 Base height: 27.75"
 Columns: 2" diameter, 14 gauge steel
 Feet: 2" diameter, 14 gauge steel, steel endcaps
 Welded Mounting Plate: 5" x 8" x 7/32" steel
 Levelers: 1-3/8" diameter, 1/4-20 x 5/8" long, allow additional 1" upward height adjustment
 Finish: powder coat
 Load capacity: 330 lbs. (200kg) vertical load rating per base

Options:

- Casters
- T or C leg
- Folding
- Bar height
- Adjustable height
- Modesty panels
- Grommets
- Wire management
- Table joiners

For easy installation, tops are pre-drilled.
 The base positioning is as following:

| | |
|-----------|-------------------------------------|
| 36" - 48" | 3.5" from the edge to column center |
| 54" | 4" from the edge to column center |
| 60" - 72" | 6" from the edge to column center |
| 84" | 12" from the edge to column center |
| 96" | 12" from the edge to column center |



Kingston Table with folded T-legs and folding laminate modesty panel