

SlimFlip Table Specifications:

Top Construction:

Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Tables 66" and longer include steel support to prevent sagging. Standard edges are T-mold and 3mm PVC. Other edges available*:

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

*Custom edges may not be available with all shapes and sizes.
See www.SpecialT.net → product page → edge tab for edge offerings.

Base Construction:

Bolted/welded
Base height: 27.75"
Columns: 2" diameter, 14 gauge steel
Feet: 2" diameter, 14 gauge steel, steel endcaps
Casters: 2" dual wheel locking casters
Finish: powder coat
Mounting beam: heavy duty tubular steel with single point positive locking release mechanism
(3) 5" x 8" x 7/32" steel hinges
5,000 lbs. vertical load rating per table



One point positive locking release mechanism

Options:

- Leveling glides
- T or Arched T- legs
- Integra folding modesty panel
- Grommets
- Wire management
- Table joiners

For easy installation, tops are pre-drilled. Legs position



**SlimFlip
with Integra Folding Modesty Panel**



Arched T-Leg Option