Feels great at home and at the office.







Comfort Ti AC23[™] from AFG. The energy savings deserve a look.







Comfort Ti AC23™ from AFG. The energy savings deserve a look.

Comfort Ti-AC23™ is a new low emissivity glass designed to maximize solar control and air conditioning efficiency in Sun Belt regions while maintaining a very attractive appearance. This next-generation low-emissivity product is the newest product innovation from industry leader AFG Glass.

With a solar heat gain coefficient of 0.23—among the lowest in the industry—the newest member of AFG's Comfort Ti™ family of low-emissivity (low-e) sputter-coated glasses is ideal for climates where air conditioning is the primary year-round energy concern. Comfort Ti-AC23, with its combination of low reflectivity, excellent light absorbing properties, and its ability to block the sun's most warming wavelengths of energy, provides one of the highest light-to-solar-gain ratios of 1.74 when deposited on clear glass. The product is ideal for coastal regions as it meets Turtle Code specifications. (<0.45 Visible Transmittance). Its unique combination of powerful solar control with a "neutral look" makes Comfort Ti-AC23 an ideal solution for a range of residential and commercial applications where heat-gain, glare, and aesthetics are a concern.

AFG Comfort Ti-AC23 Performance Data

| Glass | Air Space | Winter U-value | | Summer U-value | | % Transmittance | | | % Reflectance | | | Shading | SHGC | RHG | |
|-----------|--------------|----------------|-------|----------------|-------|-----------------|-------|----|---------------|--------|-------|-------------|------|-----|-------|
| Thickness | | Air | Argon | Air | Argon | Visible | Solar | UV | Vis out | Vis in | Solar | Coefficient | | Air | Argon |
| SGL | 1/2" | 0.30 | 0.24 | 0.28 | 0.22 | 41 | 20 | 20 | 11 | 11 | 34 | 0.27 | 0.24 | 59 | 56 |
| 1/8" | 1/2" | 0.30 | 0.24 | 0.28 | 0.22 | 40 | 19 | 19 | 12 | 11 | 33 | 0.27 | 0.23 | 58 | 55 |
| 5/32" | 1/2" | 0.29 | 0.24 | 0.28 | 0.22 | 40 | 19 | 17 | 12 | 11 | 31 | 0.27 | 0.23 | 58 | 55 |
| 3/16" | 1/2" | 0.29 | 0.24 | 0.28 | 0.22 | 39 | 18 | 16 | 13 | 11 | 29 | 0.27 | 0.24 | 58 | 56 |
| 1/4" | 1/2" | 0.29 | 0.24 | 0.28 | 0.22 | 38 | 18 | 16 | 13 | 11 | 27 | 0.27 | 0.23 | 58 | 55 |

All values are for center of glass and were obtained using LBNL's Window 5.2 software
All make-ups are Comfort Ti-AC23 outboard (coating on surface #2), 1/2" air space, and Clear inboard

