

THE EVOLUTION OF RUBBER TILE Commercial Flooring



Cert# SCS-FS-02144



DINOFLEX GROUP LP

www.dinoflex.com



COMMERCIAL RUBBER **flooring**

- OFFICES
- SCHOOLS
- MUSEUMS
- LIBRARIES
- RETAIL OUTLETS
- STAFF LOUNGES
- CALL CENTERS



Irish Moss



Sunflower



Mardi Gras



Baked Clay

floor



custom COLORS

Create your custom flooring by combining colors from our extensive palette. Available in square cut and interlocking.



- | | | | | | | | | | | | | |
|--|---|---|---|---|---|---|---|--|---|---|---|---|
|  |  |  |  |  |  |  |  |  |  |  |  |  |
| #4D Eggshell | #06 Beige | #5C Pearl | #3C Earth Yellow | #9D Yellow | #10 Orange | #7E Rose | #11 Brown | #1T Sepia Brown | #02 Red | #7H Heather Violet | #2M Kashmir | #01 Black |
|  |  |  |  |  |  |  |  |  |  |  |  |  |
| #7G Blue-Grey | #3A Capri Blue | #5D Royal Blue | #04 Blue | #08 Turquoise | #05 Grey | #07 Purple | #03 Green | #7D Pine Green | #2H Meadow | #2G Mystic Aqua | #3B Charcoal | #2K Khaki |

Spring that lasts



C U S T O M

logos

- UNIQUE
- CREATIVE
- INSPIRED
- ORIGINAL
- ARTISTIC
- APPEALING
- FUNCTIONAL

... endless possibilities!

foundation

See our **NEW**
color line coming
Spring 2011!

Visit www.dinoflex.com
for updates!



SUNFLOWER
#014E56



WHEAT
#004E55



STONE GROUND
#014E54




MUDDY WATER
#014E52



MESQUITE
#004E50




ADOBE
#004E51




BAKED CLAY
#001E53



HOT SALSA
#014E69



RAIN FOREST
#514E43



IRISH MOSS
#014E59




PIXIE MOSS
#014E60




GLADE MOSS
#004E61



SAPPHIRE HAZE
#514E62



SMOKY AZURE
#514E63



LIQUID METAL
#014E64



SPUN SILVER
#014E65




DREAM CATCHER
#514E46




CASINO ROYALE
#514E44




MARDI GRAS
#014E83



FIRE FLY
#014E41



FLAMENCO
#014E82



RIO GRANDE
#004E81



MOON BEAM
#014E42



PURPLE RAIN
#514E45

Colors shown are reproduced as closely as possible to actual product colors. Contact DINO FLEX for product samples.

PHYSICAL PROPERTIES

TEST	DESCRIPTION	UP TO 50% COLOR	50 - 100% COLOR
AATCC 134-06	Electrostatic Propensity	POS 1.6kV	
ASTM C501	Taber Abrasion (H-22)	0.8% weight loss	4.0% weight loss
ASTM D2047	Static Coefficient of Friction (JAMES MACHINE METHOD)	Dry 1.04, Wet 1.05	Dry 0.85, Wet 1.01
ASTM D2240	Hardness Shore A Durometer	64 Indentation	59 Indentation
ASTM D3676	Density Foam Test Summary	66.0 lbs/cu.ft.	78.3 lbs/cu.ft
ASTM D395B	Compression Set Under Force	96.3% Recovered	94.7% Recovered
ASTM D412	Tensile Strength	290 lbs/sq. in.	186 lbs/sq. in
ASTM D5116	Materials Emission VOC	Pass	Pass
ASTM F137	Flexibility		6mm Mandrell Passes
ASTM F150 (NFPA 99)	Electrical Resistance		
	Surface to Surface	10 ¹⁰ ohms av	10 ¹¹ ohms av
	Surface to Ground	10 ¹⁰ ohms av	10 ¹¹ ohms av
ASTM F1914-98	Short Term Indentation	.025 in (6.0%) Loss	
ASTM F1914-98	Residual Indentation	.007 in (1.7%) Loss	
ASTM F970-87	Static Load	.000 in (0.0%)	.042 in (10.6%)
ASTM F925-97	Chemical Resistance	no change	no change
ASTM G21	Mildew Resistance	No Mildew - after 14 days	No Mildew after 28 days
California 01350	(CHPS Compliant for VOC Emissions) Emission tests are performed following California Dept. of Health Services Standard Practice for the Testing of Volatile Organic Emissions from various sources using small-scale environmental chambers. CA/DHS/EHLRB/R-174, 07/15/04 (http://www.caliag.org.VOC.Section01350_7_15_2044_FINAL_PLUS_ADDENDUM-2004-01.pdf)		

SPECIFICATIONS

PRODUCT	SIZE	STANDARD THICKNESS
Interlock Tile -Loose Lay	37" x 37" = 9.5 ft ² 94cm x 94cm = 0.88 m ²	5/16", 3/8", 1/2" 8mm, 10mm, 12mm Tolerance of +/- 0.55 mm
Square Cut Tile -Glue Down	38" x 38" = 10.0 ft ² 96.5cm x 96.5cm = 0.93 m ²	5/32", 1/4", 5/16", 3/8", 1/2" 4mm, 6mm, 8mm, 10mm, 12mm Tolerance of +/- 0.55 mm

All measurements are subject to nominal variation.

10 YEAR WARRANTY

For complete specifications and technical data, please visit our website at www.dinoflex.com



DINOFLEX GROUP LP

RECYCLED RUBBER SURFACING

REPRESENTED BY

PO Box 3309
5590 - 46th Avenue, SE
Salmon Arm, BC
V1E 4S1 CANADA

TEL (250) 832-7780
FAX (250) 832-7788
TOLL FREE 1-877-713-1899
EMAIL sales@dinoflex.com

www.dinoflex.com

