


TF 3225 Ft. Hood Table Set



Size: 84" L x 35" W x 30" H.
 Shipping Weight: 2000 lbs.
 Reinforcing: 3/8", 1/4" & 1/2 Dia. steel rebar.
 Hardware: 1/2" Threaded inserts.
 Anchoring: Optional.
 Maintenance: Periodically rinse with water and mild detergent. Re-seal annually or as needed.
 Features: Ground & Polished Top Surface.

* Meets ADA Requirements

Options:

Note: Options may change without notice.
 Call to confirm current options.

Weatherstone:

Sand - Gray - Brown - Buff - Cream
 Light Charcoal - French Gray - Brick Red

Exposed Aggregate:

Tan w/Gray Matrix - Tan w/Brown Matrix
 Tan w/Sand Matrix - Misty Gray w/Gray

Smooth/Stained Concrete:

Sand - Gray - Brown - Charcoal
 Red - Yellow - Orange - Cream - Buff - Brick Red

Custom Options Available







CAUTION

DO NOT OVER
 TIGHTEN ANY BOLTS

GENERAL TABLES SPECIFICATIONS

TF 3225 Ft. Hood Set



1.1 SUMMARY

- A. Section includes: Furnish Precast Concrete Table indicated on drawings or specified herein.

1.2 REFERENCES

- A. American Society for Testing & Materials
 1. ASTM C33
 2. ASTM C150
 3. ASTM C31

1.5 SUBMITTALS

- A. Submit product data, shop drawings and Samples.
 1. Product Data: Manufacturer's specifications and technical data edited specifically for proposed system, including the following specific information:
 - a. Detailed specification of construction fabrication.
 - b. Manufacturer's installation instructions
 - c. Maintenance literature
 - d. Product warranty
 2. Shop Drawings: Indicate pertinent dimensions, general construction, component connections anchoring methods, hardware and installation procedures.
 3. Samples as requested by Architect.

1.6 QUALITY ASSURANCE

- A. Qualifications of Manufacturer: Manufacturer to be prequalified by specifier prior to bidding. Failure to comply will result in disqualification of bid. Manufacturer to have at least five years experience in the manufacturer of precast concrete tables field proven for at least five years.

1.10 WARRANTY

Manufacturer shall submit a written warranty for precast products for the period of two years upon acceptance of products.

2.1 MANUFACTURERS

- A. Acceptable manufacturer for Precast Concrete Tables to be known as Wausau Tile, Inc. Terra-Form Division.
PO Box 1520, Wausau, WI 54402-1520.
(800) 388-8728 FAX (715) 355-4627
- B. Clarification Note: Drawings and installation specification are based on manufacturers proprietary literature from Wausau Tile, Inc. Other manufacturers shall comply with minimum levels of material and detailing indicated on drawings or specified herein.
- C. All Precast products for this project shall be of one manufacturer.

2.2 MATERIALS

- A. Portland Cement: ASTM C150 specifications for Portland Cement.
- B. Aggregates: All aggregates to meet ASTM C33 specifications, to be cleaned of foreign matter and properly graded to size.
- C. Coloring: Pigments used shall be inorganic, resistant to alkalinity and used as per manufacturers recommendations.