
## TF 1023 WC AUTO ATTENDANT - SINGLE



(Note: Options may change without notice. Call to confirm current options.)

Weatherstone:

Sand - Gray - Brown - Buff - Cream - Soulard Green Light Charcoal - French Gray - Brick Red

**Exposed Aggregate:** 

Tan w/Gray Matrix - Tan w/Brown Matrix Tan w/Sand Matrix - Misty Gray w/Gray Wyoming White

<u>Granitex (GTX)</u> 2078F, 4028F, 6208F, 1168F, 2098F

Glass

Clear - Emerald - Blue - Amber Champaign - Charcoal

**Custom Options Available** 

TF 1417

Polyethylene Removeable Wash Liuqid Dispenser Material: Recycled Polyethylene Plastic

Color: May vary

TF 1417-1

Polyethylene Plastic Towel Dispenser

Material: Recycled Polyethylene Plastic

Color: May vary

Size: 21" x 25" x 35" H.

Weight: 595 lbs. Capacity: 24 gallons

Material: Reinforced Concrete Reinforcing: 1/4" Dia. steel rebar

Hardware: (4) - 1/2" Dia. Ferruled Inserts

(1) - 1/4" Dia. Zinc Alloy Inserts(3) - 3/16" Dia Zinc Alloy Inserts

(4) - 1/2" Dia ELevator Bolts; inserted on site.

(2) - 5/8" Dia. lifting inserts

(1) - Polyethylene Plastic Towel Dispenser

(1) - Polyethylene Removeable Wash Liquid Dispenser.

Packaging: Palletized

Maintenance: Rinse as needed with water & mild detergent, reseal

annually.

Anchoring: Optional

Logo Options: 12" Dia. 1/4" clear lucite silk screened with Permanent

inks. Installed with four tamper-proof rivets, or custom

cast on place logo.

TF 1610 Liner (Standard)

Size: 14-7/8" Sq. x 29-7/8" H

Weight: 10 lbs Capacity: 24 gallons

Material: Recycled Polyethylene Plastic

Color: May vary Packaging: None

TF 1467 Colonial Aluminum Top (Standard)

Size: 18" Sq.x 2"
Weight: 8 lbs.
Material: Aluminum
Color: Bronze

(Colors may change without notice.)

Hardware: (1) - Security Cable

(2) - Shouldered Allen Bolt

Opening: 8" Sq.

Packaging: Shipped in carton

Maintenance: Clean with mild soap and water
Installation: Attach to container with security cable.

## TF 1023

# Auto Attendant - Single

## 25 1/2\* HOLE OPENING 8" X 8" TF1466 18"X18" TOP 20 1/2"

TOP VIEW

# 1.1 SUMMARY

A. Section includes: Furnish Precast Concrete Waste Containers indicated on drawings or specified herein.

### 1.2 REFERENCES

- A. American Society for Testing & Materials
  - 1. ASTM C33 2. ASTM C150 3. ASTM C31

1.5 SUBMITTALS

- A. Submit product data, shop drawings and samples.
  - 1. Product Data: Manufacturer's specifications and technical data edited specifically for proposed system, including the following specific information:
    - a. Detailed specification of construction fabrication.
    - Manufacturer's installation instructions
    - Maintenance literature
    - d. Product warranty
    - Shop Drawings: Indicate pertinent dimensions, general construction, component connections anchoring methods, hardware and installation procedures.
    - Samples as requested by Architect.


#### 1.6 QUALITY ASSURANCE

A. Qualifications of Manufacturer: Manufacturer to be prequalified by specifier prior to bidding. Failure to comply will result in disqualification of bid. Manufacturer to have at least five years experience in the manufacturer of precast concrete waste containers field proven for at least five years.

# 1/2" 2 1/2" 34"

## SIDE ELEVATION

1.10 WARRANTY Manufacturer shall submit a written warranty for precast products for the



FRONT ELEVATION

period of two (2) years upon acceptance of products.

### 2.1 MANUFACTURERS

A. Acceptable manufacturer for Precast Concrete Waste Containers to be known as:

Wausau Tile, Inc.

PO Box 1520, Wausau, WI 54402-1520. (800) 388-8728 FAX (715) 355-4627

- B. Clarification Note: Drawings and installation specification are based on manufacturers proprietary literature from Wausau Tile, Inc. Other manufacturers shall comply with minimum levels of material and detailing indicated on drawings or specified herein.
- C. All Precast products for this project shall be of one manufacturer.

## 2.2 MATERIALS

- A. Portland Cement: ASTM C150 specifications for Portland Cement.
- B. Aggregates: All aggregates to meet ASTM C33 specifications, to be cleaned of foreign matter and properly graded to size.
- C. Coloring: Pigments used shall be inorganic, resistant to alkalinity and used as per manufacturers recommendations.