



EYE WITH SWAGED INTERNAL THREAD

Part # RH	Part # LH	ø Rope in mm	a	b	d1	d2	Adjustment in mm
814-0300-01	813-0300-01	3	M5	100	7	5.5	+5/-10
814-0300-02	813-0300-02	3	M5	136	7	5.5	+12/-17
814-0400-01	813-0400-01	4	M6	106	8	6.5	+4/-10
814-0400-02	813-0400-02	4	M6	135	8	6.5	+11/-17
814-0500-01	813-0500-01	5	M6	110	8	6.5	+4/-10
814-0500-02	813-0500-02	5	M6	145	8	6.5	+11/-17
814-0600-01	813-0600-01	6	M8	135	10	8.5	+4/-12
814-0600-02	813-0600-02	6	M8	173	10	8.5	+17/-25
814-0800-01	813-0800-01	8	M10	248	13	10.5	+17/-27
814-1000-01	813-1000-01	10	M14	295	20	13	+26/-40
814-1200-01	813-1200-01	12	M16	345	25	14.5	+26/-42
814-1600-01	813-1600-01	16	M20	410	32	19.3	+30/-50

AISI 316 Breaking strength: 90% of rope Max. Breaking Load



e-mail: sales@decorcable.com
Toll Free: (800)444-6271

© Copyright 2005 Carl Stahl DécorCable