
- A superior alternative to natural stone utilizing double-press technology
- Realistic colorations and texture in through-body technical Porcelain Stone®
- Coordinates with Crossville's Accent Innovations[™]
- · Rectangular shapes in four sizes add design versatility
- Ability to set with tight grout joints for more seamless designs
- Easy to maintain—no sealing or waxes required







Amber	
Size	Code
3 x 6	7A35
3 x 12	6BE3
6 x 6	5DB6
6 x 24	5C19
12 x 24	6Z27
18 x 18	4EF5
3 x 18 Single Bullnose	5A37



Rust	
Size	Code
3 x 6	7A36
3 x 12	6BE4
6 x 6	5DB7
6 x 24	5C22
12 x 24	6Z28
18 x 18	4EF6
3 x 18 Single	5A38
Rullnose	



Moss	
Size	Code
3 x 6	7A38
3 x 12	6BE6
6 x 6	5DB9
6 x 24	5C23
12 x 24	6Z30
18 x 18	4EG2
3 x 18 Single Bullnose	5A40

>500 lbf.

>150 psi

Unaffected

Resistant

< 0.20%

0.10 max.

8

>0.7

>0.6

Product Performance

Breaking Strength

Bond Strength

Frost Resistance

Water Absorption

Facial Dimension

Scratch Hardness

COF- Dry

COF- Wet

Chemical Resistance



Lead	
Size	Code
3 x 6	7A37
3 x 12	6BE5
6 x 6	5DB8
6 x 24	5C24
12 x 24	6Z29
18 x 18	4EF7
3 x 18 Single Bullnose	5A39

ASTM C648

ASTM C482

ASTM C650

ASTM C1026

ASTM C373

ASTM C499

MOH's Scale

ASTMC 1028-89

ASTM C1028-89

Sizes Available (Available in all colors)

Nominal Size	Actual Size	Metric (cm)	Thickness
3" x 6"	2-7/8" x 5-3/4"	7.3 x 14.6	3/8"
3" x 12"	2-7/8" x 11-3/4"	7.3 x 30	3/8"
6" x 6"	5-3/4" x 5-3/4"	14.6 x 14.6	3/8"
6" x 24"	5-3/4" x 23-5/8"	14.6 x 60	3/8"
12" x 24"	11-3/4" x 23-3/4"	30 x 60	3/8"
18" x 18"	17-3/4" x 17-3/4"	45 x 45	3/8"

Trim Sizes (Available in all colors)

Nominal Size	Actual Size	Metric (cm)	Thickness
3" x 18" Single	2-7/8" x 17-3/4"	9.5 x 45	3/8"



3" x 18" Single Bullnose

Shade & Texture Index

NOW has a shade variation of V4.









V1=Uniform Appearance V2=Slight Variation V3=Moderate Variation V4=Substantial Variation

Care and Maintenance

Regular cleaning is the best way to keep NOW tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressivecleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville products is available at www.crossvilleinc.com.

Recommended Usage

NOW is recommended for interior floors , walls and countertops and exterior walls in both commercial and residential applications .



