

GENERAL

Highest quality sink formed of #18 (1.2mm) gauge, type 304 (18-8) nickel bearing stainless steel. Top mount.

DESIGN FEATURES

Bowl Depths: 6-1/8".

Coved Corners: 3" (76mm) vertical and 1-3/4" (44mm) horizontal radius.

Bowl and Faucet Deck Recess: 3/16" (5mm) below outside edge of sink.

Finish: Exposed surfaces are hand blended to a lustrous satin finish.

Underside: Fully undercoated to dampen sound and reduce condensation.

This sink complies with ASME A112.19.3-2008/CSA B45.4-08.



This sink is listed by the International Association of Plumbing and Mechanical Officials as meeting the requirements of the Uniform Plumbing Code.

OTHER

Drain Openings: 3-1/2" (89mm).

NOTE: Unless otherwise specified, sink is furnished with 1 faucet hole as shown.

noie as snown.

OPTIONAL ACCESSORIES

Cutting Boards: CB816, CBS715.

Drains: LK99.

Installation hardware for thicker countertops: LK363 (up to 1-1/2" [38mm] thick; LK463 (up to 2-1/2" [66mm] thick).


Rinsing Basket: LKWRB715SS.


Utensil Caddy for Rinsing Basket: LKWUCSS.

SINK DIMENSIONS*

Model Number	Overall		Inside Bowl			Cutout in Countertop (1¹/2"[38mm] Radius Corners)		Drain	No. of 11/4" (32mm) or 11/2" (38mm) Dia. Faucet Holes	Minimum Cabinet
	L	W	L	W	D	L	W	Opening	4" (102mm) Centers	Size
LMR2013	19 ¹ / ₂ (495mm)	13 (330mm)	15 ³ / ₄ (400mm)	7 ¹ / ₂ (191mm)	6 ¹ / ₈ (181mm)	18 ⁷ / ₈ (479mm)	12 ³ / ₈ (314mm)	3½ (89mm)	1, 2, MR2 or 3	24 (610mm)

^{*}Length is left to right. Width is front to back.





HOLE DRILLING CONFIGURATIONS

