

# Strong

PORCELAIN STONE

- Shading variations within each color accentuate the look of natural slate
- All sizes are 3/8" thick for exceptional strength
- Ideal for high-traffic areas
- Five modular sizes offer unlimited design flexibility
- Easy to clean and maintain



VS100 Almond



VS101 Beige




VS102 Brown



VS103 Gallo



VS104 Verde



VS105 Nero

## Sizes Available

Surface/Texture	Size	Actual Size	Thickness
UP	6 x 6	5-3/4 x 5-3/4	3/8
UP	6 x 12	5-3/4 x 11-3/4	3/8
UP	12 x 12	11-3/4 x 11-3/4	3/8
UP	12 x 18	11-3/4 x 17-3/4	3/8
UP	18 x 18	17-3/4 x 17-3/4	3/8

## Coordinating Trim available in all colors:

3" x 12" Bullnose	3-1/4 x 11-3/4	3/8
-------------------	----------------	-----



4" x 12" Bullnose

## Product Performance

Abrasive Wear	138-198	ASTM C501
Bond Strength	>200 psi	ASTM C482
Breaking Strength	480-550 lbs.	ASTM C648
Coefficient of Friction (Dry)	>0.8	ASTM C1028-89
Coefficient of Friction (Wet)	>0.6	ASTM C1028-89
Water Absorption	<0.2% max.	ASTM C373

## Recommended Usage

Crossville porcelain stone products are recommended for interior walls and floors and exterior walls in both residential and commercial applications.

## Care and Maintenance

Regular cleaning is the best way to keep your porcelain stone looking new for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville Porcelain Stone products is available at [www.crossville-ceramics.com](http://www.crossville-ceramics.com).

## Shade & Texture Index

Strong has a shade variation of V3



V1



V2



V3



V4

V1-Uniform Appearance  
V2-Slight Variation  
V3-Moderate Variation  
V4-Substantial Variation



Crossville, Inc. • P.O. Box 1168, Crossville, TN 38557  
Phone: 931.484.2110 • Fax: 931.456.2956  
E-Mail: [crossc@crossvilleinc.com](mailto:crossc@crossvilleinc.com)  
[www.crossvilleinc.com](http://www.crossvilleinc.com)

# Strong

PORCELAIN STONE

- Shading variations within each color accentuate the look of natural slate
- All sizes are 3/8" thick for exceptional strength
- Ideal for high-traffic areas
- Five modular sizes offer unlimited design flexibility
- Easy to clean and maintain



VS100 Almond



VS101 Beige




VS102 Brown



VS103 Gallo



VS104 Verde



VS105 Nero

## Sizes Available

Surface/Texture	Size	Actual Size	Thickness
UP	6 x 6	5-3/4 x 5-3/4	3/8
UP	6 x 12	5-3/4 x 11-3/4	3/8
UP	12 x 12	11-3/4 x 11-3/4	3/8
UP	12 x 18	11-3/4 x 17-3/4	3/8
UP	18 x 18	17-3/4 x 17-3/4	3/8

## Coordinating Trim available in all colors:

3" x 12" Bullnose	3-1/4 x 11-3/4	3/8
-------------------	----------------	-----



## Product Performance

Abrasive Wear	175	ASTM C501
Bond Strength	>200 psi	ASTM C482
Breaking Strength	480-550 lbs.	ASTM C648
Coefficient of Friction (Dry)	>0.8	ASTM C1028-89
Coefficient of Friction (Wet)	>0.6	ASTM C1028-89
Water Absorption	<0.2% max.	ASTM C373

## Recommended Usage

Crossville porcelain stone products are recommended for interior walls and floors and exterior walls in both residential and commercial applications.

## Care and Maintenance

Regular cleaning is the best way to keep your porcelain stone looking new for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville Porcelain Stone products is available at [www.crossvilleinc.com](http://www.crossvilleinc.com).

## Shade & Texture Index

Strong has a shade variation of V3



V1



V2



V3



V4

V1-Uniform Appearance  
V2-Slight Variation  
V3-Moderate Variation  
V4-Substantial Variation



Crossville, Inc. • P.O. Box 1168, Crossville, TN 38557  
Phone: 931.484.2110 • Fax: 931.456.2956  
E-Mail: [crossc@crossvilleinc.com](mailto:crossc@crossvilleinc.com)  
[www.crossvilleinc.com](http://www.crossvilleinc.com)