

# BALANCE:

<b>Style Number</b>	BN
<b>Specifications</b>	
Construction	Tip-Sheared Loop
Yarn Content	XTI® Nylon
Dye Method	Beck
Machine Gauge	1/10 in. (39.4 col./10 cm)
Stitch Count	13 S.P.I. (51.2/10 cm)
Finished Pile Thickness	.148 (3.76 mm)
Average Density	8,514
Yarn Weight Tufted	36 oz./yd.2 (1220 g./m2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Pattern Repeat	Not Applicable
<b>Performance</b>	
Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP3078
<b>Warranties</b>	
Wear	10 Year Limited Warranty
Static	Lifetime Warranty
<b>Additional Information</b>	
Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at <a href="http://www.bolyu.com">www.bolyu.com</a>
Coordinating Styles	Multiple
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



# BOLYÜ

201 Princeton Boulevard  
Adairsville, Georgia 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
888 467 5075

A Beaulieu Commercial Brand