BALLINA II:

Style Number

BLL

Specifications

Construction Textured Loop Pattern

Yarn Content Zeftron® Nylon with 25% Recycled Content

Dye Method Solution

 Machine Gauge
 1/10 in. (39.4 col./10 cm.)

 Stitch Count
 13 S.P.I. (51.2/10 cm.)

 Finished Pile Thickness
 .124 in. (3.15 mm.)

Average Density 8,710

Yarn Weight Tufted 30 oz./yd.2 (1085 g./m2)

Primary Backing Polypropylene

Secondary Backing Woven Polypropylene with

Post Consumer Recycled Content

Width 12 feet (3.66m.)

Pattern Repeat .40" w x .47" l (1.01 cm. x 1.19 cm.)

Total Recycled Content 2.43%

Performance

Flame Resistance Passes (DOC FF-1-70)
Flooring Radiant Panel Class 1(ASTM E-648)

Smoke DensityLess Than 450 (ASTM E-662)CRI Green Label PlusCertification #GLP7078

Warranties

Zeftron® Stain Warranty Lifetime Stain Removal – Limited Guarantee

Zeftstat® Warranty Lifetime Carpet Static Warranty

Zeftwear® Warranty Lifetime Carpet Wear – Limited Warranty

Zeftron® CertificationClass III, Extra Heavy Traffic

enviro6ix Minimum 25% Recycled Content

Zeftron® Recycling 6ix Again®

Additional Information

Custom Colors Contact Sales Representative

Backing Options See iLoc® backings at www.bolyu.com

Coordinating Styles Multiple Samples 800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.





BOLY