

# CHAIN OF EVENTS:

Style Number	COE
<b>Specifications</b>	
Construction	Textured Loop Pattern
Yarn Content	Avalar® SDX Nylon with 25% Post Consumer Recycled Content and Puralex®
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm)
Stitch Count	12.3 S.P.I. (48.4/10 cm)
Finished Pile Thickness	.157 in. (3.99 mm)
Average Density	6,879
Yarn Weight Tufted	30 oz./yd.2 (1017 g./m2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Pattern Repeat	1.8" w x .63" l (4.6cm w x 1.6 cm l)
<b>Performance</b>	
Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP7078
<b>Warranties</b>	
Wear	10 Year Limited Warranty
Static	Lifetime Warranty
Stain	Lifetime Warranty
Colorfastness	Lifetime Warranty Against Light & Atmospheric Contaminants
<b>Additional Information</b>	
Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at <a href="http://www.bolyu.com">www.bolyu.com</a>
Coordinating Styles	Direct Effect, On The Edge, & Street Smart
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



# BÖLYÜ

201 Princeton Boulevard  
Adairsville, Georgia 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
888 467 5075