

# CUSTOM-LIFT®

## WINDING DRUM RESIDENTIAL ELEVATOR

Series 010 & 210

**CAPACITY** - 500 Lbs.

**CAR SIZE** - Maximum of 12 sq. ft.

**STOPS** - up to 6 stops

**TRAVEL** - up to 50 ft.

**SPEED** - 30 ft. per minute

**PIT DEPTH** - 6" minimum pit required

**OVERHEAD** - 8' 0" above top floor with standard 7' I.D. car (additional overhead required with some options)

**GUIDE RAIL** - 3/16" steel channel.

**MOTOR** - single speed, 2HP, instant reversing

**GEARBOX** - high-ratio, direct mounted and coupled

**DRUM** - single drum with outboard bearing

**BRAKE** - electrically released, spring applied

**SLACK CABLE/BROKEN ROPE** - twin instantaneous, broken cable and slack cable applied by a retained compression spring.

**TRUCK** - heavy gauge steel with hi-density synthetic guides and rollers

**CABLE** - two 1/4" 8x19 GAC/SA157

**ELECTRIC SUPPLY** - 230 volts, single phase, 60 hertz. For 208 volts, single phase, a Buck Boost transformer must be added. A separate 120-volt circuit is required for cab lighting

**CONTROLS** - fully automatic at car and landings, car light switch, emergency stop switch, in-use indicator at landings

**SIGNAL SYSTEM** - wall mount phone jack, emergency alarm

**HOISTWAY DOOR INTERLOCKS** - required at each landing

**MACHINE LOCATION** - multiple remote locations

**EMERGENCY LOWERING** - manual hand wheel

**CAR** - Frameless car with accordion gate standard

**ADDITIONAL OPTIONS** - are available, for details contact your local dealer.

