

FIRST IMPRESSION:

Style Number

FIM

Specifications

Construction	Loop Pattern
Yarn Content	Zeftron® Nylon with 25% recycled content
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	13 S.P.I. (51.2/10 cm.)
Finished Pile Thickness	.134 in.
Average Density	8,597
Yarn Weight Tufted	32 oz./yd.2 (1085 g./m2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	iLoc® ES with Post Consumer Recycled Content
Pattern Repeat	3.75" w x 0" l (9.5 cm. x 0 cm.)

Performance

Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP7078

Warranties

Zeftron® Stain Warranty	Lifetime Stain Removal – Limited Guarantee
Zeftstat® Warranty	Lifetime Carpet Static Warranty
Zeftwear® Warranty	Lifetime Carpet Wear – Limited Warranty
Zeftron® Certification	Class III, Extra Heavy Traffic
envirobix®	Minimum 25% Recycled Content
Zeftron® Recycling	6ix Again®
Edge Ravel	Lifetime Warranty, seam sealer required
Delamination	Lifetime Warranty, under normal use
Tuft Bind	Lifetime Warranty, not to zipper, wet or dry

Additional Information

Custom Colors	Contact Mill Representative
Backing Options	See iLoc® Folder
Coordinating Styles	Panache
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



BÖLYÜ

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075