

FLAIR TILE:

Style Number

FRT

Specifications

Construction	Interloop Pattern
Yarn Content	Zeftron® Nylon with 25% recycled content
Dye Method	Solution/Space
Machine Gauge	1/12 in. (47.2 col./10 cm.)
Stitch Count	11 S.P.I. (43.3/10 cm.)
Finished Pile Thickness	.122 in. (3.09 mm.)
Average Density	8,115
Yarn Weight Tufted	28 oz./yd.2 (949 g./m2)
Primary Backing	Non Woven
Secondary Backing	Nexterra® with 85% Post Consumer Recycled Content and Puralex®
Modular Tile Width	24" x 24" (61 cm. x 61 cm.)

Performance

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
CRI Green Label Plus	Certification #GLP8595

Warranties

Zeftron® Stain Warranty	Lifetime Stain Removal – Limited Guarantee
Zeftstat® Warranty	Lifetime Carpet Static Warranty
Zeftwear® Warranty	Lifetime Carpet Wear – Limited Warranty
Zeftron® Certification	Class III, Extra Heavy Traffic
envirobix™	Minimum of 25% recycled content
Zeftron® Recycling	6ix Again®
Edge Ravel	Lifetime Warranty
Delamination	Lifetime Warranty, under normal use
Tuft Bind	Lifetime Warranty

Additional Information

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.bolyu.com
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



BOLYÜ

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075