



Type II™ DrainCore Drainage Dimpleboard

PRODUCT DESCRIPTION

Type II is a moderate duty impermeable polymeric sheet that while under heat and pressure is formed into a dimpled drainage core.

The core is then bonded to a single layer of non-woven filter fabric. The filter fabric retains soil and sand particles as well as freshly placed concrete or grout, allowing water to pass into the drainage core.

PURPOSE:

Type II is used as a protection and drainage roll and is engineered to provide ample strength to protect membranes against back fill soil and sediment and to provide excellent drainage capabilities.

ADVANTAGES:

- Higher compressive strength for greater depth
- Strong resistance to hydrostatic pressure
- High flow dimpled drainage core
- Protects waterproofing membrane
- Easy installation

LEEDS DATA:

Type II DrainCore is considered a GREEN product and can be used toward LEEDS building credits.

SPECIFICATION:

CORE

- Color – Black
- Thickness –ASTM D-1777 - .40 in.
- Drainage Capacity - ASTM D-4716 (HG=1) –21 g/pm/ft width
- Compression Strength –ASTM D-1621 –15,000 psf

FABRIC

- Color – White Fabric
- Flow – ASTM D-4491 – 140 g/min/ft²
- Puncture – ASTM D-4833 – 65 lbs.
- AOS(EOS) – 70 U.S. Sieve
- Grab Tensile – ASTM D-4632 – 100 lbs.

PACKAGING:

4' x 50' roll

COVERAGE:

200 ft² / roll

PREP/APPLICATION (With Membrane):

Application of waterproofing membrane should be completed.

Starting at a corner, install the Type II horizontally against the waterproofing membrane with the non-woven filter fabric side facing out-ward.

Extend the roll from the top of the footer to finished grade. When two edges come together from two separate rolls, overlap the dimples to create a continuous coverage of the wall.

For good adherence, **with** a membrane, apply uniform pressure throughout the surface area, not just the edges and corners. If needed, secure rolls to the wall using powder actuated mechanical fasteners.

For good adherence, **without** a membrane, mechanical fasteners will be required to secure rolls to the wall. When using mechanical fasteners install top fasteners within the top 4" (102 mm).

If the roll overlaps the membrane once you have reached the grade line, a utility knife or similar tool can be used to cut the rolls to the correct height.

BACKFILLING/DRAINAGE:

Residential - Backfilling should begin no sooner than 24 hours after the installation of the board, but must be backfilled within 15 days.

CLEAN UP:

Disposal methods must be in compliance with all federal, state and local laws and regulations.

PRODUCT HANDLING/STORAGE:

- Do not smoke while handling
- When installing wear respirator
- No special storage requirements
- Wash thoroughly with soap and water after handling

WARNING/DANGERS:

- Keep away from sparks, open flames, or any heat source
- Dust might create mechanical irritation

PRODUCT ONLY WARRANTY:

We warrant the product to be of good quality and manufactured to meet published physical properties and quality control standards.

Except as specifically provided herein, Marflex makes no warranty, express, implied or oral including but not limited to any warranty or merchantability, fitness for a particular purpose, usage of trade, course of dealing or course of performance in connection with this agreement. In no event shall Marflex be liable on any such warranty with respect to the product. Marflex shall not be liable for incidental or consequential damages including, but not limited to damages of the structure, its replacement, contents or personal injury. Some states do not allow limitations on how long an implied warranty lasts or allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

HEALTH AND SAFETY INFORMATION IS GIVEN IN THE MATERIAL SAFETY DATA SHEET AND THE PRODUCT DATA SHEET AVAILABLE FOR THIS PRODUCT. THESE SHOULD BE READ AND UNDERSTOOD BEFORE USING THIS PRODUCT.

Marflex Building Solutions
6866 Chrisman Lane, Middletown, OH 45042
(800) 498-1411 | (513) 422-7285 | Fax (513) 422-7282
E-mail: technicalsupport@mar-flex.com
Web-site: www.MarflexBuildingSolutions.com

Rev. 10-09.1