

# HERRINGBONE:

**Style Number**

HRB

## Specifications

<b>Construction</b>	Textured Loop Pattern
<b>Yarn Content</b>	Zeftron® Nylon with 25% recycled content
<b>Dye Method</b>	Solution
<b>Machine Gauge</b>	1/10 in. (39.4 col./10 cm.)
<b>Stitch Count</b>	11 S.P.I. (43.3/10 cm.)
<b>Finished Pile Thickness</b>	.122 in. (3.10 mm.)
<b>Average Density</b>	9.443
<b>Yarn Weight Tufted</b>	32 oz./yd.2 (1085 g./m2)
<b>Primary Backing</b>	Masterline® Woven Primary
<b>Secondary Backing</b>	iLoc® ES with Post Consumer Recycled Content
<b>Width</b>	12 feet (3.66m.)
<b>Pattern Repeat</b>	9" w x 0" l (22.9 cm. x 00 cm.)

## Performance

<b>Static Control</b>	Less Than 3.5 k.v. Step
<b>Flame Resistance</b>	Passes (DOC FF-1-70)
<b>Flooring Radiant Panel</b>	Class 1 (ASTM E-648)
<b>Smoke Density</b>	Less Than 450 (ASTM E-662)
<b>CRI Green Label Plus</b>	Certification #GLP7078

## Warranties

<b>Zeftron® Stain Warranty</b>	Lifetime Stain Removal – Limited Guarantee
<b>Zeftstat® Warranty</b>	Lifetime Carpet Static Warranty
<b>Zeftwear® Warranty</b>	Lifetime Carpet Wear – Limited Warranty
<b>Zeftron® Certification</b>	Class III, Extra Heavy Traffic
<b>Zeftron® Recycling</b>	6ix Again®
<b>Edge Ravel</b>	Lifetime Warranty, seam sealer required
<b>Delamination</b>	Lifetime Warranty, under normal use
<b>Tuft Bind</b>	Lifetime Warranty, not to zipper, wet or dry

## Additional Information

<b>Custom Colors</b>	Contact Sales Representative
<b>Backing Options</b>	See iLoc® backings at <a href="http://www.bolyu.com">www.bolyu.com</a>
<b>Coordinating Styles</b>	Basketry
<b>Samples</b>	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



# B O L Y Ü

201 Princeton Boulevard  
Adairsville, Georgia 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
888 467 5075