

# MODERN FORM:

<b>Style Number</b>	MDF
<b>Specifications</b>	
<b>Construction</b>	Tip-Sheared Loop Pattern
<b>Yarn Content</b>	Avalar® SDX Nylon with 25% Pre-Consumer Recycled Content and Puralex®
<b>Dye Method</b>	Solution
<b>Machine Gauge</b>	1/10 in. (39.4 col./10 cm.)
<b>Stitch Count</b>	12.3 S.P.I. (48.4/10 cm.)
<b>Finished Pile Thickness</b>	.140 in. (3.6 mm.)
<b>Average Density</b>	8,228
<b>Yarn Weight Tufted</b>	32 oz./yd.2 (1085 g./m2)
<b>Primary Backing</b>	Masterline® Woven Primary
<b>Secondary Backing</b>	Woven Polypropylene with Post Consumer Recycled Content
<b>Width</b>	.80" w x .65" l (2.03 cm. w x 1.7 cm.)
<b>Total Recycled Content</b>	2.36%
<b>Performance</b>	
<b>Static Control</b>	Less Than 3.5 k.v. Step
<b>Flame Resistance</b>	Passes (DOC FF-1-70)
<b>Flooring Radiant Panel</b>	Class 1 (ASTM E-648)
<b>Smoke Density</b>	Less Than 450 (ASTM E-662)
<b>Soil Resistance</b>	Commercial Anti-Soil Protection
<b>CRI Green Label Plus</b>	Certification #GLP7078
<b>Warranties</b>	
<b>Wear</b>	10 Year Limited Warranty
<b>Static</b>	Lifetime Limited Warranty
<b>Stain</b>	Lifetime Limited Warranty
<b>Colorfastness</b>	Lifetime Limited Warranty Against Light & Atmospheric Contaminants
<b>Additional Information</b>	
<b>Custom Colors</b>	Contact Sales Representative
<b>Backing Options</b>	See iLoc® Backings at <a href="http://www.bolyu.com">www.bolyu.com</a>
<b>Coordinating Styles</b>	Fine-Tuned and Visual Order
<b>Samples</b>	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



# BOLYU

201 Princeton Boulevard  
Adairsville, Georgia 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
888 467 5075