

ON THE EDGE:

Style Number	OTE
Specifications	
Construction	Textured Loop Pattern
Yarn Content	Avalar® SDX Nylon with 25% Recycled Content and Puralex® Solution
Dye Method	1/10 in. (39.4 col./10 cm)
Machine Gauge	12 S.P.I. (47.2/10 cm)
Stitch Count	.150 in. (3.81 mm)
Finished Pile Thickness	7,200
Average Density	30 oz./yd.2 (1017 g./m2)
Yarn Weight Tufted	Masterline® Woven Primary
Primary Backing	Woven Polypropylene with Post Consumer Recycled Content
Secondary Backing	.80" w x .50" l (2 cm w x 1.3 cm l)
Pattern Repeat	
Performance	
Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP7078
Warranties	
Wear	10 Year Limited Warranty
Static	Lifetime Warranty
Stain	Lifetime Limited Warranty
Colorfastness	Lifetime Limited Warranty Against Light & Atmospheric Contaminants
Additional Information	
Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.bolyu.com
Coordinating Styles	Chain of Events, Direct Effect & Street Smart
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



BOLYÜ

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075

A Beaulieu Commercial Brand