

RHYTHMICS TILE:

Style Number

RTM

Specifications

Construction

Patterned Loop

Yarn Content

Avalar® X Nylon with Post Industrial Recycled Content

Dye Method

Solution/Space

Machine Gauge

1/12 in. (47.2 col./10 cm.)

Stitch Count

10.6 S.P.I. (41.7/10 cm.)

Finished Pile Thickness

.136 in. (3.45 mm)

Average Density

6,353

Yarn Weight Tufted

24 oz./yd.2 (813.5g./m2)

Primary Backing

Non Woven

Secondary Backing

Nexterra with 85% Post Consumer Recycled Content and Puralex®

Modular Tile Width

24" x 24" (61 cm. x 61 cm.)

Total Recycled Content

64-67%

Performance

Static Control

Less Than 3.5 k.v. Step

Flame Resistance

Passes (DOC FF-1-70)

Flooring Radiant Panel

Class 1 (ASTM E-648)

Smoke Density

Less Than 450 (ASTM E-662)

Soil Resistance

Commercial Anti-Soil Protection

CRI Green Label Plus

Certification #GLP8595

Warranties

Wear

Lifetime Limited Warranty

Static

Lifetime Warranty

Edge Ravel

Lifetime Warranty

Delamination

Lifetime Warranty, under normal use

Tuft Bind

Lifetime Warranty

Stain

Lifetime Limited Warranty

Additional Information

Custom Colors

Contact Sales Representative

Backing Options

See iLoc® backings at www.bolyu.com

Samples

800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



B Ō L Y Ü

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075