

# SIMPLICITY:

## Style Number

SMP

### Specifications

Construction	Pattern Cut/Loop
Yarn Content	Antron® Legacy nylon
Dye Method	75% Solution Dyed, 25% Yarn Dyed
Machine Gauge	1/12 in. (47.2col./10 cm.)
Stitch Count	13.8 S.P.I. (54.3/10 cm.)
Finished Pile Thickness	.130 in. (3.3 mm.)
Average Density	8,862
Yarn Weight Tufted	32 oz./yd.2 (1084 g./m2)
Primary Backing	Non Woven
Secondary Backing	Nexterra®-85% Post Consumer Recycled Content with Puralex®
Modular Tile Width	24" x 24" (61 cm. x 61 cm.)

### Performance

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	DuraTech® Patented Soil Resistance
CRI Green Label Plus	Certification #GLP8595

### Warranties

Wear	10 Year Limited Warranty
Edge Ravel	Lifetime of Carpet
Delamination	Lifetime of Carpet, under normal use
Tuft Bind	Lifetime of Carpet

### Additional Information

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® Backings at bolyu.com
Coordinating Styles	Multiple
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

# BOLYÜ

Beaulieu Commercial (USA)  
201 Princeton Boulevard  
Adairsville, Georgia 30103  
800 451 1250

Beaulieu Commercial (Canada)  
335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
888 467 5075