SUMMER WOOD:

Style Number SU

Specifications

ConstructionPattern Cut/LoopYarn ContentAntron ® Legacy Nylon

Dye Method Beck Dyed

Machine Gauge1/10 in. (39.4 col./10 cm.)Stitch Count15 S.P.I. (59/10 cm.)Finished Pile Thickness.21 in. (5.33mm.)

Average Density 6,103

Yarn Weight Tufted34.3 oz./yd.2 (1162 g./m2)Primary BackingMasterline® Woven PrimarySecondary BackingWoven Polypropylene with

Post Consumer Recycled Content

Width 12 feet (3.66m.)

Pattern Repeat 24" w x 19.2" | (61 cm. x 48.7 cm.)

Performance

Static ControlLess Than 3.5 k.v. StepFlame ResistancePasses (DOC FF-1-70)Flooring Radiant PanelClass 1(ASTM E-648)

Smoke Density Less Than 450 (ASTM E-662)

Soil Resistance DuraTech® Patented Soil Resistance

CRI Green Label Plus Certification #GLP3078

Warranties

Wear 10 Year Limited Warranty

Additional Information

Custom ColorsContact Sales RepresentativeBacking OptionsSee iLoc® Backings at bolyu.com

Coordinating StylesMultipleSamples800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.





BOLYÜ

201 Princeton Boulevard Adairsville, Georgia 30103 800 451 1250 335 Roxton Street Acton Vale, Quebec Canada JOH 1A0 888 467 5075