

WINTER SOLSTICE:

Style Number

WS

Specifications

Construction	Pattern Cut/Loop
Yarn Content	Antron® Legacy Nylon
Dye Method	Beck Dyed
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	15 S.P.I. (59/10 cm.)
Finished Pile Thickness	.21 in. (5.33mm.)
Average Density	6,103
Yarn Weight Tufted	34.3 oz./yd.2 (1162 g./m2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Width	12 feet (3.66m.)
Pattern Repeat	24" w x 19.2" l (61 cm. x 48.7 cm.)

Performance

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	DuraTech® Patented Soil Resistance
CRI Green Label Plus	Certification #GLP3078

Warranties

Wear	10 Year Limited Warranty
------	--------------------------

Additional Information

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® Backings at bolyu.com
Coordinating Styles	Multiple
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



BOLYÜ

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075

A Beaulieu Commercial Brand