

SPECIFICATIONS

Construction	Textured Loop Pattern
Yarn Content	Cambridge Approved Nylon
Dye Method	Solution / Space Dye
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	11 S.P.I. (43.3/10 cm.)
Finished Pile Thickness	.134 in. (3.4 mm.)
Average Density	6,985
Yarn Weight Tufted	26 oz./yd.2 (881 g./m.2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Width	12 feet (3.66 m.)
Pattern Repeat	.40" W x .36" L (1.0 cm. x .91 cm.)
Total Recycled Content	2.58%

PERFORMANCE

Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil
CRI Green Label Plus	Certification # GLP7078

WARRANTIES

Wear	10 Year Limited Warranty
-------------	--------------------------

ADDITIONAL INFORMATION

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.cambridgecarpet.com
Coordinating Styles	Multiple
Samples	800 451 1250



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Carpet Design® 2003 Beaulieu Group, LLC.

CAPITAL GAINS

style # 6CPG

Cambridge®

201 Princeton Boulevard
P.O. Box 1110
Adairsville, GA 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada JOH 1A0
888 467 5075

www.cambridgecarpet.com

A Beaulieu Commercial Brand