SPECIFICATIONS

ConstructionTextured Loop PatternYarn ContentCambridge Approved Nylon

Dye Method Solution

Machine Gauge1/10 in (39.4 in./10cm)Stitch Count10 S.P.I (39.4/ 10cm)Finished Pile Thickness.077 in. (1.96 mm)

Average Density 10,286

Yarn Weight Tufted 22 oz. /yd.² (746 g/m²)

Primary Backing Non Woven

Secondary Backing Nexterra® with 85% Post Consumer

Content and Puralex®

Width 24" x 24" (61 cm. x 61 cm.)

Total Recycled Content 63%

PERFORMANCE

Static ControlLess Than 3.5 K.V. StepFlame ResistancePasses (DOC FF-1-70)Flooring Radiant PanelClass 1 (ASTM E-648)Smoke DensityLess than 450 (ASTM E-662)Soil ResistanceCommercial Anti-Soil ProtectionCRI Green LabelCertification # GLP8595

WARRANTIES

Wear Lifetime Limited Warranty
Static Lifetime Warranty
Tuft Bind Lifetime Warranty
Edge Ravel Lifetime Warranty

Zippering Lifetime Warranty, not to zipper wet or dry

Pilling & Fuzzing Lifetime Warranty

DelaminationLifetime Warranty, under normal use

Dimensional Stability Lifetime Warranty

ADDITIONAL INFORMATION

Custom Colors Contact Sales Representative

Backing Options See iLoc® backings at www.cambridgecarpet.com

Additives Puralex[®] is a refresher that is

environmentally friendly and specially formulated to help purify the air.

Samples 800 451 1250





Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Carpet Design® 2007 Beaulieu Group, LLC.

EPIC

style # 6TEPC

Cambridge®

201 Princeton Boulevard P.O. Box 1110 Adairsville, GA 30103 800 451 1250

335 Roxton Street Acton Vale, Quebec Canada JOH 1A0 888 467 5075

www.cambridgecarpet.com

A Beaulieu Commercial Brand